

Granville Hypalube SL SS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

PRODUCT DESCRIPTION

Granville Hypalube SL 5W/30 is a semi synthetic engine oil designed to provide maximum protection for modern engines requiring a low viscosity oil. It is suitable for lean burn, multi-valve, fuel injected, twin cam, turbo charged and Ford Zetec engines.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: SL/CF

ACEA: A5/B5



* Image for illustrative purposes only.

PRODUCT BENEFITS

- * Ensures lubricant performance over extended drain intervals
- * Excellent high & low temperature performance
- * Outstanding fuel efficiency
- * Effective environmental protection

PRODUCT USAGE

For engines where this specification lubricant is required.

DIRECTIONS FOR USE

As recommended by the engine manufacturer.

STORAGE INSTRUCTIONS

Store upright and sealed in a cool, dry place out of the reach of children.

SHELF LIFE

5 years from date of manufacture.

Appearance : Amber liquid
Odour : Characteristic

SIZE	PART NO	BARCODE
1 Litre	0427	5020618004271
5 Litre	0435	5020618004356
20 Litre	0262	5020618002628
199 Litre	0426	5020618004264



Granville Hypalube SL SS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

Solubility : Insoluble in water

Percentage of Base Oil : More Than 80%

Percentage of Biodiesel : Nil

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s	9.3	<12.5	10.38
Cold Cranking Viscosity	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	8		10.62
HTHS Viscosity	ASTM D4683	mPa.s	2.9	3.5	
NOACK Volatility	ASTM D5800	%		13	
Kinematic Viscosity at 40°C	ASTM D445	mm ² /s			62.95
Density	ASTM D792	@ 15°C			0.862
Pour Point	ASTM D97	°C		-35	

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

