

## TECHNICAL DATA

# Granville LS 80W/90

1Litre & 5 Litre

#### PRODUCT DESCRIPTION

Granville LS 80W/90 is a specially formulated extreme pressure gear oil for optimum performance of limited slip differentials. LS 80W/90 is a blend of high quality base oils, performance EP additives and specially selected friction modifiers to provide a lubricant with exacting requirements for limited slip operations.

### RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: GL-5

#### **PRODUCT BENEFITS**

- \* Reduces whining and chattering
- \* Ensures clutch plates slide smoothly
- \* Outstanding extremes of temperature protection



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	1636	5020618016366
5 Litre	1715	5020618017158

#### **PRODUCT USAGE**

Suitable for limited slip differentials fitted to cars, vans, trucks, buses and agricultural equipment.

#### **DIRECTIONS FOR USE**

As recommended by the vehicle manufacturer.

#### STORAGE INSTRUCTIONS

As recommended by the vehicle manufacturer.

#### SHELF LIFE

5 years from date of manufacture.

Revision: 3 | Date: 11/11/2016

Appearance : Amber liquid

Odour : Characteristic

Solubility : Insoluble in water





### TECHNICAL DATA

# Granville LS 80W/90

1Litre & 5 Litre

Percentage of Base Oil : More Than 70%

Percentage of Biodiesel : Nil

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°c	ASTM D445	mm²/s	13.5	<18.5	15.98
Kinematic Viscosity at 40°c	ASTM D445	mm²/s			153.42
Density	ASTM D792	@ 15°c			0.893

#### SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

#### TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

