

Granville FS-PX 0W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

PRODUCT DESCRIPTION

Granville FS-PX 0W/30 is a fully synthetic mid-SAPS engine oil specially formulated to meet the very latest specifications and fuel efficiency targets required by Peugeot/Citroen power units including Blue HDi and Pure Tech engine types. Suitable for use in Petrol and Diesel engines where specified.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C2

PSA: B71 2312



* Image for illustrative purposes only.

PRODUCT BENEFITS

- * Fully synthetic
- * Reduces fuel consumption
- * Stable lubricant film at high temperatures
- * Suitable for extended oil drain intervals

PRODUCT USAGE

For use in engines where this viscosity and specification is required including petrol and diesel engines including those fitted with three way catalysts and diesel particulate filters.

DIRECTIONS FOR USE

Use as per the engine manufacturers recommendations

STORAGE INSTRUCTIONS

Store sealed and upright in a cool dry place out of the reach of children



Granville Oil & Chemicals Ltd.

29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL ENGLAND

Tel: +44 (0)1709 890099 • www.granvilleoil.com

Granville FS-PX 0W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

SHELF LIFE

5 years from date of manufacture

Appearance : Clear amber liquid

Odour : Characteristic

Solubility : Insoluble in water

Percentage of Biodiesel : Nil

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s	9.3	<12.5	9.76
Cold Cranking Viscosity	ASTM D4684	mPa.s		6200	
Total Base Number	ASTM D2896	mg KOH/g	6		8.46
Pour Point	ASTM D97	°C		-35	
HTHS Viscosity	ASTM D4683	mPa.s	2.9		
NOACK Volatility	ASTM D5800	%		13	
Kinematic Viscosity at 40°C	ASTM D445	mm ² /s			52.22
Density	ASTM D792	@ 15°C			0.847

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

