

Granville Hy-Vis Hydraulic 46

20 Litre & 199 Litre

PRODUCT DESCRIPTION

Hypalube Hy-vis 46 hydraulic oil is formulated for use in a wide range of agricultural, commercial and industrial applications, it offers excellent pumpability and protects against oxidation and corrosion.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

AFNOR: NF E 48603
David Brown: S1.53.101
Denison Filterability: TP021000
DIN: 51524 Part 2
Vickers: 1.286.S & 1.286.S3
ISO: 6734-4 HM

PRODUCT BENEFITS

- *Excellent pumpability
- *Protects against oxidation and corrosion.

STORAGE INSTRUCTIONS

Store upright and sealed in a cool place and out of the reach of children

SHELF LIFE

5 years from date of manufacture

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water
Percentage of Biodiesel	: Nil



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
20 Litre	0724	5020618007241
199 Litre	0140	5020618001409



Granville Hy-Vis Hydraulic 46

20 Litre & 199 Litre

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 40°C	ASTM D445	mm ² /s	41.4	50.6	46.65
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s			6.88
Density	ASTM D792	@ 15°C			0.877

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

