

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830  
Issue date: 6/20/2023 Version: 1.2

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form	: Mixture
Trade name	: G+Pro Brake & Parts Cleaner
Product code	: 0969, 1035
Type of product	: Mixture of hydrocarbons

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Intended for general public	
Main use category	: Professional use, Consumer use
Use of the substance/mixture	: Cleaning/washing agents and additives
Function or use category	: Cleaning/washing agents and additives

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

##### Granville Oil & Chemicals Ltd

29 Goldthorpe Ind. Est.,  
Goldthorpe,  
Rotherham,  
South Yorkshire,  
S63 9BL  
T 01709 890099  
lab@granvilleoil.com

#### 1.4. Emergency telephone number

Emergency number :  
Contact The National Poisons Information Service (dial 111, 24 h service). See section 4  
"First aid measures".

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 1	H224
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Aspiration hazard, Category 1	H304
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411

Full text of H-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

Extremely flammable liquid and vapour. May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye irritation. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

## 2.2. Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]



Hazard pictograms (CLP)

GHS02 : GHS07 GHS08 GHS09

Signal word (CLP)

: Danger

Contains

: ≥30% aliphatic hydrocarbons.

Hazard statements (CLP)

: H224 - Extremely flammable liquid and vapour.  
H304 - May be fatal if swallowed and enters airways.  
H315 - Causes skin irritation.  
H319 - Causes serious eye irritation.  
H336 - May cause drowsiness or dizziness.  
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P101 - If medical advice is needed, have product container or label at hand.  
P102 - Keep out of reach of children.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P235 - Keep cool.  
P271 - Use only outdoors or in a well-ventilated area.  
P301+P310+P331 - IF SWALLOWED: Immediately call a doctor. Do NOT induce vomiting.  
P391 - Collect spillage.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.

## 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C7-C9 n-alkanes, Isoalkanes, Cyclics,	EC-No.: 920-750-0 REACH-no: 01-2119473851-33	≥ 50	Flam. Liq. 2, H225 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411
Hydrocarbons, C6, isoalkanes, <5% n-hexane	EC-No.: 931-254-9 REACH-no: 01-2119484651-34	≥ 10 – < 30	Flam. Liq. 2, H225 Asp. Tox. 1, H304 STOT SE 3, H336

First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: Risk of lung oedema.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	EC-No.: 927-510-4 REACH-no: 01-2119475515-33	≥ 10 – < 30	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411
propan-2-ol; isopropyl alcohol; isopropanol	CAS-No.: 67-63-0 EC-No.: 200-661-7 EC Index-No.: 603-117-00-0 REACH-no: 01-2119457558-25	≥ 10 – < 30	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
Treat symptomatically.	

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable liquid and vapour.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

### 5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

### 6.1.1. For non-emergency personnel

Emergency procedures

: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

### 6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

## 6.2. Environmental precautions

Avoid release to the environment.

## 6.3. Methods and material for containment and cleaning up

For containment

: Collect spillage.

Methods for cleaning up

: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information

: Dispose of materials or solid residues at an authorized site.

## 6.4. Reference to other sections

For further information refer to section 13.

# SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

Precautions for safe handling

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

Hygiene measures

: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

## 7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Ground/bond container and receiving equipment.

Storage conditions

: Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

## 7.3. Specific end use(s)

No additional information available

# SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

### 8.1.1. National occupational exposure and biological limit values

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)

United Kingdom - Occupational Exposure Limits

Local name

Propan-2-ol

WEL TWA (OEL TWA) [1]	999 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	400 ppm
WEL STEL (OEL STEL)	1250 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

No additional information available

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

**Appropriate engineering controls:**

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

**Personal protective equipment:**

Gloves.

**Personal protective equipment symbol(s):**



#### 8.2.2.1. Eye and face protection

**Eye protection:**

Safety glasses

#### 8.2.2.2. Skin protection

**Skin and body protection:**

Wear suitable protective clothing

**Hand protection:**

Protective gloves

#### 8.2.2.3. Respiratory protection

**Respiratory protection:**

In case of insufficient ventilation, wear suitable respiratory equipment

#### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

**Environmental exposure controls:**

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Odour	: aromatic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: -25 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: 0.7
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: < 20.5 mm <sup>2</sup> /s
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Extremely flammable liquid and vapour.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

LD50 dermal rat	2800 – 3100 mg/kg bodyweight Animal: rat
LC50 Inhalation - Rat	> 23.3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

#### Hydrocarbons, C7-C9 n-alkanes, Isoalkanes, Cyclics,

LD50 dermal rat	2800 – 3100 mg/kg bodyweight Animal: rat
LC50 Inhalation - Rat	> 23.3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

#### propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)

LD50 oral rat	4700 – 5800 mg/kg
LD50 dermal rabbit	13000 mg/kg
LC50 Inhalation - Rat [ppm]	10000 ppm/4h

Skin corrosion/irritation : Causes skin irritation.  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitisation : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified Reproductive toxicity : Not classified  
STOT-single exposure : May cause drowsiness or dizziness.

#### Hydrocarbons, C6, isoalkanes, <5% n-hexane

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

#### Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

#### Hydrocarbons, C7-C9 n-alkanes, Isoalkanes, Cyclics,

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

#### propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure : Not classified

#### Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

LOAEC (inhalation, rat, vapour, 90 days)	16.6 mg/l air Animal: rat, Animal sex: male
NOAEC (inhalation, rat, vapour, 90 days)	3.3 mg/l air Animal: rat, Animal sex: male

#### Hydrocarbons, C7-C9 n-alkanes, Isoalkanes, Cyclics,

NOAEC (inhalation, rat, vapour, 90 days)	24.3 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
--	---

Aspiration hazard : May be fatal if swallowed and enters airways.

## SOLVENT BRAKE CLEANER

Viscosity, kinematic	< 20.5 mm <sup>2</sup> /s
----------------------	---------------------------

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

Not rapidly degradable

#### Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

LOEC (chronic)	0.32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
----------------	--

NOEC (chronic)	0.17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
----------------	--

#### Hydrocarbons, C7-C9 n-alkanes, Isoalkanes, Cyclics,

LOEC (chronic)	0.32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
----------------	--

NOEC (chronic)	0.17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
----------------	--

#### propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)

LC50 - Fish [1]	9640 – 10400 mg/l
-----------------	-------------------

EC50 - Crustacea [1]	7550 – 13299 mg/l
----------------------	-------------------

IC50, algae	> 1000 (72 Hours)
-------------	-------------------

### 12.2. Persistence and degradability

#### propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)

Biodegradation	> 97 % within 28 days
----------------	-----------------------

### 12.3. Bioaccumulative potential

#### propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)

Bioaccumulative potential	Does not bioaccumulate.
---------------------------	-------------------------

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects



No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
 Additional information : Flammable vapours may accumulate in the container.

## SECTION 14: Transport information


In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
UN 1268	UN 1268	UN 1268	UN 1268	UN 1268
<b>14.2. UN proper shipping name</b>				
PETROLEUM PRODUCTS, N.O.S. (CONTAINS : propan-2-ol; isopropyl alcohol; isopropanol)	PETROLEUM PRODUCTS, N.O.S. (CONTAINS : propan-2-ol; isopropyl alcohol; isopropanol)	Petroleum distillates, n.o.s. (CONTAINS : propan-2-ol; isopropyl alcohol; isopropanol)	PETROLEUM PRODUCTS, N.O.S. (CONTAINS : propan-2-ol; isopropyl alcohol; isopropanol)	PETROLEUM PRODUCTS, N.O.S. (CONTAINS : propan-2-ol; isopropyl alcohol; isopropanol)
<b>Transport document description</b>				
UN 1268 PETROLEUM PRODUCTS, N.O.S. (CONTAINS : propan-2-ol; isopropyl alcohol; isopropanol), 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS	UN 1268 PETROLEUM PRODUCTS, N.O.S. (CONTAINS : propan-2-ol; isopropyl alcohol; isopropanol), 3, II, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1268 Petroleum distillates, n.o.s. (CONTAINS : propan-2-ol; isopropyl alcohol; isopropanol), 3, II, ENVIRONMENTALLY HAZARDOUS	UN 1268 PETROLEUM PRODUCTS, N.O.S. (CONTAINS : propan-2-ol; isopropyl alcohol; isopropanol), 3, II, ENVIRONMENTALLY HAZARDOUS	UN 1268 PETROLEUM PRODUCTS, N.O.S. (CONTAINS : propan-2-ol; isopropyl alcohol; isopropanol), 3, II, ENVIRONMENTALLY HAZARDOUS
<b>14.3. Transport hazard class(es)</b>				
3	3	3	3	3
<b>14.4. Packing group</b>				
II	II	II	II	II
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

## 14.6. Special precautions for user

### Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 664
Limited quantities (ADR)	: 500ml
Excepted quantities (ADR)	: E3
Packing instructions (ADR)	: P001
Mixed packing provisions (ADR)	: MP7, MP17
Portable tank and bulk container instructions (ADR)	: T11
Portable tank and bulk container special provisions (ADR)	: TP1, TP8
Tank code (ADR)	: L4BN
Vehicle for tank carriage	: FL
Transport category (ADR)	: 1
Special provisions for carriage - Operation (ADR)	: S2, S20
Hazard identification number (Kemler No.)	: 33



Orange plates	:
Tunnel restriction code (ADR)	: D/E
EAC code	: 3YE

### Transport by sea

Limited quantities (IMDG)	: 500 ml
Excepted quantities (IMDG)	: E3
Packing instructions (IMDG)	: P001
Tank instructions (IMDG)	: T11
Tank special provisions (IMDG)	: TP1, TP8
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: E
Properties and observations (IMDG)	: Immiscible with water.

### Air transport

PCA Excepted quantities (IATA)	: E3
PCA Limited quantities (IATA)	: Forbidden
PCA limited quantity max net quantity (IATA)	: Forbidden
PCA packing instructions (IATA)	: 351
PCA max net quantity (IATA)	: 1L
CAO packing instructions (IATA)	: 361
CAO max net quantity (IATA)	: 30L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3H

### Inland waterway transport

Classification code (ADN)	: F1
Limited quantities (ADN)	: 500 ml
Excepted quantities (ADN)	: E3
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 1

### Rail transport

Classification code (RID)	: F1
Limited quantities (RID)	: 500ml
Excepted quantities (RID)	: E3
Packing instructions (RID)	: P001
Mixed packing provisions (RID)	: MP7, MP17
Portable tank and bulk container instructions (RID)	: T11
Portable tank and bulk container special provisions	: TP1, TP8

---

(RID)

Tank codes for RID tanks (RID) : L4BN  
Transport category (RID) : 1  
Hazard identification number (RID) : 33

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### 15.1.1. EU-Regulations

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

Contains no substance(s) listed on the REACH Candidate List

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

##### 15.1.2. National regulations

France	
Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

##### Germany

Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG)  
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG)

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

##### Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed

SZW-lijst van reprotoxische stoffen –  
Vruchtbaarheid : None of the components are listed

SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

##### Denmark

Class for fire hazard : Add boilingpoint

Store unit : Add boilingpoint

Classification remarks : Add boilingpoint; Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

##### Switzerland

Storage class (LK) : LK 3 - Flammable liquids

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## Full text of H- and EUH-statements

Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
-------------------	---

## SECTION 16: Other information

### Abbreviations and acronyms

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)

TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

#### Full text of H- and EUH-statements

Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 1	Flammable liquids, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Safety Data Sheet (SDS) Detergent Regulations

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.