

Granville Oil & Chemicals Ltd.

29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL, ENGLAND Tel: +44(0)1709 890099 • granvilleoil.com

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 9/5/2023 Revision date: 4/16/2025 Supersedes version of: 9/5/2023 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : G+ Pro Quick Start

Product code : 1090

UFI : QJ10-0040-U00F-AX3Y

Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Intended for general public

1.3. Details of the supplier of the safety data sheet

Granville Oil & Chemicals Ltd

29 Goldthorpe Ind. Est Goldthorpe Rotherham South Yorkshire S63 9BL

T 01709 890099 lab@granvilleoil.com

Veedol Ireland Ltd

77 Camden Street Lower Saint Kevin's Dublin Ireland D02 XE80

T +353 151 363 47

1.4. Emergency telephone number

Emergency number : +44 (0)1709 890099

Country/Area	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity – Single exposure, Category 3, H336
Narcosis H412

Hazardous to the aquatic environment – Chronic Hazard,

Category 3

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





Granville Oil & Chemicals Ltd.

29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL, ENGLAND Tel: +44(0)1709 890099 • granvilleoil.com

GHS02 GHS07

Signal word (CLP) : Danger
Contains : ACETONE

UFI : QJ10-0040-U00F-AX3Y

Hazard statements (CLP) : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H315 - Causes skin irritation. H319 - Causes serious eye irritation. H336 - May cause drowsiness or dizziness.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use. P271 - Use only outdoors or in a well-ventilated area.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
PETROLEUM GASES, LIQUEFIED	CAS-No.: 68476-85-7 EC-No.: 270-704-2 EC Index-No.: 649-202-00-6	30 – 50	Flam. Gas 1, H220
ACETONE substance with a Community workplace exposure limit	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330-	10 – 30	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
DIETHYL ETHER	CAS-No.: 60-29-7 EC-No.: 200-467-2 EC Index-No.: 603-022-00-4	10 – 30	Flam. Liq. 1, H224 Acute Tox. 4 (Oral), H302 STOT SE 3, H336
HYDROCARBONS,C6-C7,N-ALKANES,ISOALKANES,CYCLICS,<5% N-HEXANE	EC-No.: 921-024-6 REACH-no: 2119475514-35- XXXX	10 – 30	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
HYDROCARBONS, C6, ISOALKANES, <5% N-HEXANE	CAS-No.: 64742-49-0 EC-No.: 931-254-9 REACH-no: 01-2119484651- 34	1 – 10	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Product subject to CLP Annex I, item 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16



Granville Oil & Chemicals Ltd.

29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL, ENGLAND Tel: +44 (0)1709 890099 • granvilleoil.com

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get

medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

First-aid measures for first aider : First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness. Symptoms/effects after inhalation : None under normal conditions.

Symptoms/effects after skin contact : Irritation.
Symptoms/effects after eye contact : Eye irritation.

Symptoms/effects after ingestion : None under normal conditions.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurised container: May burst if heated.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper

protective equipment, including respiratory protection.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.

Absorb spillage to prevent material damage.

For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing

dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

4/16/2025 (Revision date) GB - en 3/12



Granville Oil & Chemicals Ltd.

29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL, ENGLAND Tel: +44(0)1709 890099 • granvilleoil.com

6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to

prevent migration and entry into sewers or streams. Stop leak without risks if possible.

Methods for cleaning up : Mechanically recover the product.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use. Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal

protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this

product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked

up. Store in a well-ventilated place. Keep container tightly closed.

Packaging materials : Store always product in container of same material as original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

ACETONE (67-64-1)		
United Kingdom - Occupational Exposure Limits		
Local name	Acetone	
WEL TWA (OEL TWA) 1210 mg/m³		
	500 ppm	
WEL STEL (OEL STEL)	3620 mg/m³	
	1500 ppm	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
PETROLEUM GASES, LIQUEFIED (68476-85-7)		
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) < 1750 mg/m³		
WEL STEL (OEL STEL) < 2180 mg/m³		



Granville Oil & Chemicals Ltd.

29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL, ENGLAND Tel: +44(0)1709 890099 • granvilleoil.com

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protection equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Personal protective equipment symbol(s):







Eye and face protection

Eye protection:

Safety glasses

Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Colour : clear.
Odour
Odour threshold : Not available
Melting point : Not available
Freezing point : Not available
Boiling point : Not available

Flammability : Extremely flammable aerosol.

Explosive properties : Pressurised container: May burst if heated.

Lower explosion limit : Not available Upper explosion limit : Not available Flash point : < 23 °C : Not available Auto-ignition temperature : Not available Decomposition temperature : Not available рΗ : Not available Viscosity, kinematic Solubility : Not available Partition coefficient n-octanol/water (Log Kow) : Not available Vapour pressure : Not available : Not available Vapour pressure at 50°C : Not available Density : Not available Relative density Not available Relative vapour density at 20°C Particle characteristics : Not applicable



Granville Oil & Chemicals Ltd.

29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL, ENGLAND Tel: +44(0)1709 890099 • granvilleoil.com

9.2. Other information

Information with regard to physical hazard classes

% of flammable ingredients : 97.2945 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified Acute toxicity (dermal) : Not classified Acute toxicity (inhalation) : Not classified

ACETONE (67-64-1)		
5800 mg/kg bodyweight Animal: rat, Animal sex: female		
> 15800 mg/kg		
LC50 Inhalation - Rat 76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4		

Skin corrosion/irritation : Causes skin irritation.

ACE	IONE	(67-64-1)
		`	•

pH 5 – 6

Serious eye damage/irritation : Causes serious eye irritation.

ACETONE (67-64-1)

pH 5 – 6

Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

ACETONE (67-64-1))
-----------	----------	---

LOAEL (animal/female, F0/P)

11298 mg/kg bodyweight Animal: mouse, Animal sex: female

NOAEL (animal/male, F0/P)

900 mg/kg bodyweight Animal: rat, Animal sex: male

STOT-single exposure : May cause drowsiness or dizziness.



Granville Oil & Chemicals Ltd.

29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL, ENGLAND Tel: +44(0)1709 890099 • granvilleoil.com

ACETONE (67-64-1)		
STOT-single exposure	May cause drowsiness or dizziness.	
HYDROCARBONS,C6-C7,N-ALKANES,ISOALK	ANES,CYCLICS,<5% N-HEXANE	
STOT-single exposure	May cause drowsiness or dizziness.	
HYDROCARBONS, C6, ISOALKANES, <5% N-HEXANE (64742-49-0)		
STOT-single exposure	May cause drowsiness or dizziness.	
DIETHYL ETHER (60-29-7)		
STOT-single exposure	May cause drowsiness or dizziness.	
STOT-repeated exposure : Not classified Aspiration hazard : Not classified		
GRANVILLE G+PRO QUICK START 1090 (LABELLED) NPD11946		
Vaporizer	Aerosol	

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short–term : Not classified

(acute)

Hazardous to the aquatic environment, long-term : Harr

(chronic)

: Harmful to aquatic life with long lasting effects.

ACETONE (67-64-1)		
LC50 - Fish [1] 5540 mg/l (Oncorhynchus mykiss; 96 h)		
LC50 - Fish [2]	11000 mg/l (Alburnus alburnus; 96 h)	
LOEC (chronic) > 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'		
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	

12.2. Persistence and degradability

GRANVILLE G+PRO QUICK START 1090 (LABELLED) NPD11946			
Persistence and degradability Not rapidly degradable			
ACETONE (67-64-1)	ACETONE (67-64-1)		
Persistence and degradability Not rapidly degradable			
HYDROCARBONS,C6-C7,N-ALKANES,ISOALKANES,CYCLICS,<5% N-HEXANE			
Persistence and degradability Not rapidly degradable			
HYDROCARBONS, C6, ISOALKANES, <5% N-HEXANE (64742-49-0)			
Persistence and degradability Not rapidly degradable			
DIETHYL ETHER (60-29-7)			
Persistence and degradability Not rapidly degradable			



Granville Oil & Chemicals Ltd.

29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL, ENGLAND Tel: +44(0)1709 890099 • granvilleoil.com

PETROLEUM GASES, LIQUEFIED (68476-85-7)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

ACETONE (67-64-1)	
Partition coefficient n-octanol/water (Log Kow)	-0.24

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation : Disposal must be done according to official regulations.

Dispose of contents/container in accordance with licensed collector's sorting instructions. Waste treatment methods

Sewage disposal recommendations Disposal must be done according to official regulations. Product/Packaging disposal recommendations : Disposal must be done according to official regulations.

Additional information : Do not re-use empty containers.

SECTION 14: Transport information

ADR	
AUIT	
14.1. UN number or ID number	
UN 1950	
14.2. UN proper shipping name	
AEROSOLS	
Transport document description	
UN 1950 AEROSOLS, 2.1, (D)	
14.3. Transport hazard class(es)	
2.1	
2	
14.4. Packing group	
Not applicable	



Granville Oil & Chemicals Ltd.

29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL, ENGLAND Tel: +44(0)1709 890099 • granvilleoil.com

ADR

14.5. Environmental hazards

Dangerous for the environment: No

No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR) : 5F

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 1I Excepted quantities (ADR) : E0

Packing instructions (ADR) : P207, LP200 Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR) : MP9

Transport category (ADR) : 2

Special provisions for carriage - Packages (ADR) : V14

Special provisions for carriage - Loading, unloading : CV9, CV12

and handling (ADR)

Special provisions for carriage - Operation (ADR) : S2 Tunnel restriction code (ADR) : D

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported within 24 hours.



Granville Oil & Chemicals Ltd.

29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL, ENGLAND Tel: +44(0)1709 890099 • granvilleoil.com

Name	CAS-No.	Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.		Category, Subcategory	Threshold	Annex
Acetone		67-64-1	2914 11 00	Category 3		Annex I
Ethyl ether	Diethyl ether	60-29-7	2909 11 00	Category 3		Annex I

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:		
ACGIH	American Conference of Government Industrial Hygienists	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
BLV	Biological limit value	
BOD	Biochemical oxygen demand (BOD)	
CAS-No.	Chemical Abstract Service number	
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008	
COD	Chemical oxygen demand (COD)	
CSA	Chemical safety assessment	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC-No.	European Community number	
EC50	Median effective concentration	
ED	Endocrine disruptor	
EN	European Standard	
EWC	European waste catalogue	
IARC	International Agency for Research on Cancer	
IATA	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Median lethal concentration	
LD50	Median lethal dose	
LOAEL	Lowest Observed Adverse Effect Level	



Granville Oil & Chemicals Ltd.

29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL, ENGLAND Tel: +44(0)1709 890099 • granvilleoil.com

Abbreviations and acronyms:		
Log Kow	Partition coefficient n-octanol/water (Log Kow)	
Log Pow	Partition coefficient n-octanol/water (Log Pow)	
MAK	maximum workplace concentration	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
N.O.S.	Not Otherwise Specified	
OECD	Organisation for Economic Co-operation and Development	
OEL	Occupational Exposure Limit	
OSHA	Occupational Safety Health Administration	
PBT	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
PPE	Personal protection equipment	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
SDS	Safety Data Sheet	
STP	Sewage treatment plant	
TF	Technical function	
ThOD	Theoretical oxygen demand (ThOD)	
TLM	Median Tolerance Limit	
TWA	Time Weighted Average	
VOC	Volatile Organic Compounds	
vPvB	Very Persistent and Very Bioaccumulative	
UFI	Unique Formula Identifier	

Full text of H- and EUH-statements:		
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Asp. Tox. 1	Aspiration hazard, Category 1	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Gas 1	Flammable gases, Category 1	
Flam. Liq. 1	Flammable liquids, Category 1	
Flam. Liq. 2	Flammable liquids, Category 2	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis	
H220	Extremely flammable gas.	
H222	Extremely flammable aerosol.	
H224	Extremely flammable liquid and vapour.	
H225	Highly flammable liquid and vapour.	
H229	Pressurised container: May burst if heated.	



Granville Oil & Chemicals Ltd.

29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL, ENGLAND Tel: +44(0)1709 890099 • granvilleoil.com

Full text of H- and EUH-statements:		
H302	Harmful if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H319	Causes serious eye irritation.	
H336	May cause drowsiness or dizziness.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.