



SAFETY DATA SHEET
G+PRO WHITE GREASE WITH PTFE

Page: 1
Compilation date: 14/12/2017
Revision date: 12/01/2018
Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: G+PRO WHITE GREASE WITH PTFE
Product code: 1080

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Granville Oil & Chemicals Ltd.
Unit 29 Goldthorpe Industrial Estate
Goldthorpe
Rotherham
South Yorkshire
S63 9BL
United Kingdom
Tel: +44 (0)1709 890099
Fax: +44 (0)1709 891121
Email: technical@granvilleoil.com

1.4. Emergency telephone number

Emergency tel: +44 (0)1709 890099
(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Chronic 2: H411; Flam. Aerosol 1: H222; -:
H229

Most important adverse effects: Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H222: Extremely flammable aerosol.
H229: Pressurised container: May burst if heated
H315: Causes skin irritation.
H336: May cause drowsiness or dizziness.
H411: Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET
G+PRO WHITE GREASE WITH PTFE

Page: 2

Hazard pictograms: GHS02: Flame
GHS07: Exclamation mark
GHS09: Environmental



Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211: Do not spray on an open flame or other ignition source.
P251: Do not pierce or burn, even after use.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.
PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

NAPHTHA (PETROLEUM) HYDROTREATED, LIGHT, LOW BOILING POINT

EINECS	CAS	PBT / WEL	CLP Classification	Percent
265-151-9	64742-49-0	-	Flam. Liq. 2: H225; Asp. Tox. 1: H304; Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Chronic 2: H411	30-50%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.
Drench the affected skin with running water for 10 minutes or longer if substance is still on skin.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

[cont...]

SAFETY DATA SHEET
G+PRO WHITE GREASE WITH PTFE

Page: 3

Delayed / immediate effects: No data available.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Extremely flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of ignition. If outside do not approach from downwind.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Do not use equipment in clean-up procedure which may produce sparks. Clean-up should be dealt with only by qualified personnel familiar with the specific substance.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Smoking is forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from direct sunlight. Keep away from sources of ignition.

Suitable packaging: Must only be kept in original packaging.

[cont...]

SAFETY DATA SHEET
G+PRO WHITE GREASE WITH PTFE

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

NAPHTHA (PETROLEUM) HYDROTREATED, LIGHT, LOW BOILING POINT

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
EU	1200mg/m ³	-	-	-

DNEL/PNEC Values

Hazardous ingredients:

NAPHTHA (PETROLEUM) HYDROTREATED, LIGHT, LOW BOILING POINT

Type	Exposure	Value	Population	Effect
DNEL	Dermal	773ml/kg/day	Workers	Systemic
DNEL	Inhalation	2035mg/m ³	Workers	Systemic
DNEL	Dermal	699mg/kg/day	Consumers	Systemic
DNEL	Inhalation	608mg/m ³	Consumers	Systemic
DNEL	Oral	699mg/kg/day	Consumers	Systemic

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Respiratory protection not required.

Hand protection: Chemically resistant gloves

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: Prevent from entering in public sewers or the immediate environment.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Aerosol

Colour: White

Odour: Characteristic odour

Flash point°C: -60

SAFETY DATA SHEET
G+PRO WHITE GREASE WITH PTFE

Page: 5

9.2. Other information

Other information: No data available

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable at room temperature. Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

NAPHTHA (PETROLEUM) HYDROTREATED, LIGHT, LOW BOILING POINT

DERMAL	RAT	LD50	2000	mg/kg
GASES	RAT	4H LC50	>20	mg/l
ORAL	RAT	LD50	2000	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: No data available.

[cont...]

SAFETY DATA SHEET
G+PRO WHITE GREASE WITH PTFE

Page: 6

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

NAPHTHA (PETROLEUM) HYDROTREATED, LIGHT, LOW BOILING POINT

ALGAE	72H IC50	<10	mg/l
DAPHNIA	48H EC50	<10	mg/l
FISH	96H LC50	<10	mg/l

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Recovery operations: Not applicable.

Disposal of packaging: Not applicable.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

[cont...]

SAFETY DATA SHEET
G+PRO WHITE GREASE WITH PTFE

Page: 7

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H222: Extremely flammable aerosol.
H225: Highly flammable liquid and vapour.
H229: Pressurised container: May burst if heated
H304: May be fatal if swallowed and enters airways.
H315: Causes skin irritation.
H336: May cause drowsiness or dizziness.
H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.