

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1 Product identifier

Product Name ABRO Fuel Injector Cleaner

Product code IC-509

Unique Formula Identifier (UFI) 1MG0-00A4-200M-TWPJ

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s) Fuel Additive
Uses Advised Against Not known.

1.3 Details of the supplier of the safety data sheet

Manufacturer

Company Identification ABRO Industries Inc
Address of Manufacturer 3580 Blackthorn Court

South Bend

USA

Postal code 46628

Telephone:  $+1\,574-232-8289$  Fax Not known. E-mail abro@abro.com

Office hours

Supplier

Company Identification Granville Oil & Chemicals Ltd Address of Supplier 29 Goldthorpe Ind. Est.,

Goldthorpe, Rotherham, South Yorkshire,

Journ Tork.

Postal code S63 9BL

Telephone: +44 (0)1709 890099

Fax Not known.

E-mail lab@granvilleoil.com
Office hours 08:00 - 17:00

1.4 Emergency telephone number

Emergency Phone No. +44 111
National response centre NHS Direct

## **SECTION 2: HAZARDS IDENTIFICATION**

# 2.1 Classification of the substance or mixture

Regulation (EC) No. 1272/2008 (CLP) Flam. Liq. 3 :Flammable liquid and vapour.

Asp. Tox. 1: May be fatal if swallowed and enters airways.

Skin Irrit. 2: Causes skin irritation.

Eye Irrit. 2: Causes serious eye irritation.

Acute Tox. 4: Harmful if inhaled.





STOT SE 3: May cause respiratory irritation. May cause drowsiness or dizziness.

Muta. 2: Suspected of causing genetic defects.

Carc. 2: Suspected of causing cancer.

Aquatic Acute 1: Very toxic to aquatic life.

Aquatic Chronic 3: Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

According to Regulation (EC) No. 1272/2008 (CLP)

Product Name ABRO Fuel Injector Cleaner

Contains Fuel oil, No 2 Gasoil - unspecified [A distillate oil having a minimum viscosity of

32,6 SUS at 37,7  $^{\circ}$  C (100  $^{\circ}$  F) to a maximum of 37,9 SUS at 37,7  $^{\circ}$  C (100  $^{\circ}$  F).]

Hazard Pictogram(s)









Signal Word(s)

Danger

Hazard Statement(s) H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H341: Suspected of causing genetic defects.

H351: Suspected of causing cancer.

H410: Very toxic to aquatic life with long lasting effects.

Precautionary Statement(s)

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P271: Use only outdoors or in a well-ventilated area.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection. P301+P310: IF SWALLOWED: Immediately call a POISON CENTRE/doctor.

P331: Do NOT induce vomiting.

P403+P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

Unique Formula Identifier (UFI)

1MG0-00A4-200M-TWPJ

2.3 Other hazards

None known.



# 2.4 Additional Information

For full text of H/P Statements see section 16.

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

# 3.1 Substances

Not applicable.

#### 3.2 Mixtures

| HAZARDOUS INGREDIENT(S)   | CAS No.    | EC No. /<br>REACH<br>Registration<br>No. | %W/<br>W     | Hazard Statement(s)   | Hazard<br>Pictogram(s)  |
|---|------------|--|--------------|---|-------------------------|
| Fuel oil, No 2 Gasoil - unspecified [A distillate oil having a minimum viscosity of 32,6 SUS at 37,7 °C (100 °F) to a maximum of 37,9 SUS at 37,7 °C (100 °F).]   | 68476-30-2 |  | =<98         | Carc. 2 H351  | GHS08                   |
| Paraffins (petroleum), normal C5-20   | 64771-72-8 |  | 0.3-<br>0.6  | Asp. Tox. 1 H304  | GHS08                   |
| naphthalene   | 91-20-3    |  | 0.01-<br>0.5 | Acute Tox. 4 H302<br>Carc. 2 H351<br>Aquatic Acute 1 H400<br>Aquatic Chronic 1 H410 | GHS08<br>GHS07<br>GHS09 |
| Xylene  | 1330-20-7  |  | 0.2 -        | Flam. Liq. 3 H226<br>Acute Tox. 4 H312<br>Skin Irrit. 2 H315<br>Acute Tox. 4 H332   | GHS02<br>GHS07          |
| ethylbenzene  | 100-41-4   |  | 0.1          | Flam. Liq. 2 H225<br>Acute Tox. 4 H332  | GHS02<br>GHS07          |
| Distillates (petroleum), hydrotreated light Kerosine - unspecified [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 150 °C to 290 °C (302 °F to 554 °F).] | 64742-47-8 |  | 0.02-<br>0.1 | Asp. Tox. 1 H304  | GHS08                   |



| HAZARDOUS INGREDIENT(S) | CAS No.   | Specific Concentration Limit | M-factor | ATE                          |
|-------------------------|-----------|------------------------------|----------|------------------------------|
| naphthalene             | 91-20-3   |                              |          | Acute Tox. 4 (H302) : 500    |
|                         |           |                              |          |                              |
| Xylene                  | 1330-20-7 |                              |          | Acute Tox. 4 (H312) : 1100   |
|                         |           |                              |          | Acute Tox. 4 (H332) : 11.000 |
|                         |           |                              |          |                              |
| ethylbenzene            | 100-41-4  |                              |          | Acute Tox. 4 (H332) : 11.000 |
|                         |           |                              |          |                              |

Contains no non-classified vPvB substances.

Contains no non-classified substances with a Union workplace exposure limit.

For full text of H/P Statements see section 16.

### SECTION 4: FIRST AID MEASURES

#### 4.1 Description of first aid measures

Inhalation Remove to fresh air. If not breathing, institute rescue breathing. If breathing is

difficult, ensure airway is clear and give oxygen. If heart has stopped,

immediately begin cardiopulmonary resuscitation (CPR). Keep affected person

warm and at rest. GET IMMEDIATE MEDICAL ATTENTION.

Skin Contact Immediately wash exposed skin with plenty of soap and water while removing

contaminated clothing and shoes. Get medical attention if irritation persists. Place contaminated clothing in closed container until cleaned or discarded. If clothing is to be laundered, inform the person performing the operation of

contaminant's hazardous properties.

Eye Contact Flush immediately with large amounts of water for at least 15 minutes. Eyelids

should be held away from the eyeball to ensure thorough rinsing. GET

IMMEDIATE MEDICAL ATTENTION.

Ingestion Do not induce vomiting. If spontaneous vomiting is about to occur, place victim's

head below knees. If victim is drowsy or unconscious, place on the left side with head down. Never give anything by mouth to an unconscious person. Keep affected person warm and at rest. GET IMMEDIATE MEDICAL ATTENTION

# 4.2 Most important symptoms and effects, both acute and delayed

May cause irritation.

### 4.3 Indication of any immediate medical attention and special treatment needed

If ingested this material represents a significant aspiration and chemical pneumonitis hazard. Induction of emesis is not recommended.

# SECTION 5: FIREFIGHTING MEASURES

# 5.1 Extinguishing media

Suitable Extinguishing media For small fires, CO2, dry chemical, foam or water spray.

For large fires, water spray, fog or foam.

### 5.2 Special hazards arising from the substance or mixture



Flammable liquid and vapour. Combustion produces carbon monoxide, aldehydes, aromatic and other hydrocarbons.

#### 5.3 Advice for firefighters

Avoid using straight water streams. Water spray and foam must be applied carefully to avoid frothing and from as far a distance as possible. Avoid excessive water spray application. Keep surrounding area cool with water spray from a distance and prevent further ignition of combustible material. Keep runoff water out of sewers and water sources.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Chemical splash goggles. Chemical-resistant protective suit. Boots. Chemical-resistant gloves. Self-contained breathing apparatus (SCBA) should be used to avoid inhalation of the product. Suggested protective clothing might not be adequate. Consult a specialist before handling this product. CAUTION: The protection provided by air-purifying respirators is limited. Use a positive pressure air-supplied respirator if there is any potential for an uncontrolled release, if exposure levels are not known, or if concentrations exceed the protection limits of air-purifying respirator.

#### 6.2 Environmental precautions

Avoid release to the environment. Spillages or uncontrolled discharges into watercourses must be alerted to the appropriate regulatory body.

#### 6.3 Methods and material for containment and cleaning up

Large Spill

Stop leak if without risk. Eliminate all ignition sources. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

Small Spill

Stop leak if without risk. Eliminate all ignition sources. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Use spark-proof tools and explosion proof equipment. Dispose of via a licensed waste disposal contractor.

#### 6.4 Reference to other sections

See Also Section 8, 13.

#### **SECTION 7: HANDLING AND STORAGE**

### 7.1 Precautions for safe handling

Isolate from sources of heat, sparks, and open flame. Open container in a well-ventilated area. Avoid breathing vapours and thermal decomposition products.



Keep containers closed when not in use. Vapours are heavier than air and will tend to accumulate in low areas. Avoid use in confined areas without adequate ventilation. Areas of inadequate ventilation could contain concentrations high enough to cause eye irritation, headaches, respiratory discomfort, or nausea. Carefully evaluate processes using this product at elevated temperatures to ensure safe operating conditions. Electrostatic build-up may occur when pouring or transferring this product from its container.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

### 7.3 Specific end use(s)

Fuel Additive

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

### 8.1.1 Occupational Exposure Limits

| Occupational Exposure Limits |           |                |                |       |         |      |  |
|------------------------------|-----------|----------------|----------------|-------|---------|------|--|
| SUBSTANCE.                   | CAS No.   | LTEL (8 hr TWA | LTEL (8 hr TWA | STEL  | STEL    | Note |  |
|                              |           | ppm)           | mg/m³)         | (ppm) | (mg/m³) |      |  |
| Xylene, o-,m-,p- or mixed    | 1330-20-7 | 50             | 220            | 100   | 441     | Sk,  |  |
| isomers                      |           |                |                |       |         | BMGV |  |
| Ethylbenzene                 | 100-41-4  | 100            | 441            | 125   | 552     | Sk   |  |

Region Source

United Kingdom UK Workplace Exposure Limits EH40/2005 (Fourth edition, published 2020)

Remark Notes

Sk Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to

systemic toxicity.

BMGV Biological monitoring guidance values are listed in Table 2.

| Biological Exposure Indices |           |         |        |                 |                                 |         |
|-----------------------------|-----------|---------|--------|-----------------|---------------------------------|---------|
| Substances                  | CAS       | Samplin | Tissue | Control         | Biological monitoring guidance  | Comment |
|                             | Number    | g       | S      | parameters      | value                           | S       |
| Polycyclic aromatic         | 91-20-3   | Post    | urine  | 1-hydroxypyrene | 4 $\mu$ mol 1-hydroxypyrene/mol |         |
| hydrocarbons (PAHs)         |           | shift   |        |                 | creatinine                      |         |
| Xylene, o-, m-, p- or mixed | 1330-20-7 | Post    | urine  | methyl hippuric | 650 mmol methyl hippuric        |         |
| isomers                     |           | shift   |        | acid            | acid/mol creatinine             |         |



Remark Notes

#### 8.2 Exposure controls

8.2.1. Appropriate engineering controls Use non-sparking ventilation systems, approved explosion-proof equipment, and

intrinsically safe electrical systems. Use with ventilation, local exhaust ventilation or breathing protection. A washing facility/water for eye and skin

cleaning purposes should be present.

8.2.2. Personal protection equipment Wash hands, forearms, and face thoroughly after handling chemical products,

before eating, smoking and using the lavatory and at the end of the working

period. Appropriate techniques should be used to remove potentially

contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye Protection Wear eye protection with side protection (EN166).

Skin protection Wear protective clothing and gloves: Impervious gloves (EN 374).



Respiratory protection Use approved organic vapor chemical cartridge or supplied air respirators when

material produces vapours that exceed permissible limits or excessive vapours are generated. Observe respirator assigned protection factors (APFs) criteria cited in federal OSHA 1910.134. Self-contained breathing apparatus should be

used for firefighting.

Thermal hazards None known.

8.2.3. Environmental Exposure Controls Spillages or uncontrolled discharges into watercourses must be alerted to the appropriate regulatory body.

Local or general exhaust required when using at elevated temperatures that

generate vapours or mists.

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

Physical stateLiquid.ColourClear Red.OdourPetroleum odour.Melting point/freezing pointNot known.Boiling point or initial boiling point andNot known.

boiling range

Flammability Not known.

Lower and upper explosion limit Not known.

Flash Point > 120.00 F (48.9 C) Method Used: Pensky-Marten Closed Cup.





Auto-ignition temperature Not known.

Decomposition Temperature Not known.

pH Not known.

Kinematic Viscosity Not known.

Solubility Solubility (Water) : Insoluble.
Solubility (Other) : Not known.

er Not known.

Partition coefficient n-octanol/water

(log value)

Vapour pressure

Not known.

Density and/or relative density 6.74 - 7.32 LBS/GAL at 70.0 F (21.1 C)

Relative vapour density Not known.
Particle characteristics Not known.

9.2 Other information

None.

#### SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

None anticipated.

10.2 Chemical Stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose.

10.4 Conditions to avoid

Excessive heat, sources of ignition and open flames.

10.5 Incompatible materials

Strong oxidizers such as nitrates, perchlorates, chlorine, fluorine.

10.6 Hazardous decomposition products

Combustion produces carbon monoxide, aldehydes, aromatic and other

hydrocarbons.

#### SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity - Ingestion Calculation method : Not classified.

 ${\it Calculation method: Calculated acute\ toxicity\ estimate\ (ATE)\ \ Calc\ ATE\ -\ 100000}$ 

Acute toxicity - Skin Contact Calculation method : Not classified.

Calculation method: Calculated acute toxicity estimate (ATE) Calc ATE - 275000

Acute toxicity - Inhalation Self classification: Harmful if inhaled.

Skin corrosion/irritation Self classification: Causes skin irritation.

Serious eye damage/irritation Self classification: Causes serious eye irritation.

Skin sensitization data Calculation method : Not classified.

Respiratory sensitization data Calculation method : Not classified.

Germ cell mutagenicity Self classification: Suspected of causing genetic defects.

Carcinogenicity Calculation method: Suspected of causing cancer.

Page: 8 - 15 Revision: 1 - Replaces:



Reproductive toxicity Calculation method : Not classified.

Lactation Calculation method : Not classified.

STOT - single exposure Self classification: May cause respiratory irritation. May cause drowsiness or

dizziness

STOT - repeated exposure Calculation method : Not classified.

Aspiration hazard Self classification: May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Not known.

### SECTION 12: ECOLOGICAL INFORMATION

#### 12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Toxicity - Aquatic invertebrates Not known.

Toxicity - Fish Not known.

Toxicity - Algae Not known.

Toxicity - Sediment Compartment Not classified.

Toxicity - Terrestrial Compartment Not classified.

12.2 Persistence and degradability

Not known.

12.3 Bioaccumulative potential

Not known.

12.4 Mobility in soil

Not known.

12.5 Results of PBT and vPvB assessment

Not known.

12.6 Endocrine disrupting properties

None known.

12.7 Other adverse effects

Not known.

### **SECTION 13: DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

Dispose of contents in accordance with local, state or national legislation. Recycle only completely emptied packaging. Containers must not be punctured or destroyed by burning, even when empty. Do not allow to enter drains, sewers or watercourses. Do NOT landfill. Normal disposal is via incineration operated by an accredited disposal contractor. Send to a licensed recycler, reclaimer or incinerator. Dispose of this material and its container to hazardous or special waste collection point. Dispose at suitable refuse site.

### 13.2 Additional Information

Disposal should be in accordance with local, state or national legislation.

### SECTION 14: TRANSPORT INFORMATION

Page: 9 - 15 Revision: 1 - Replaces:



14.1 UN number or ID number

UN No. 1993

14.2 UN proper shipping name

UN proper shipping name FLAMMABLE LIQUID, N.O.S.

14.3 Transport hazard class(es)

ADR/RID

Mixed Packing Instructions for P001 IBC03 LP01 R001

Packages

Special Packing Provisions for

Packages

Mixed Packing Instructions for MP19

Packages

Packing Instructions for Portable Tanks  $\ T4$ 

Special Provisions for Portable Tanks TP1 TP29
Tank Code for Tanks LGBF

Special Provisions for Tanks

Vehicle for Tank Carriage FL
ADR Transport Category 3
Tunnel Restriction Code D/E
Special Provisions for Carriage - V12

Packages

Special Provisions for Carriage - Bulk

Special Provisions for Carriage -Loading, Unloading and Handling

Special Provisions for Carriage - S2

Operation

ADR HIN 30

IMDG

IMDG Class 3

Special Provisions 274, 601
Limited Quantities 5 L
Excepted Quantities E1

Mixed Packing Instructions for P001 IBC03 LP01 R001

Packages

Special Packing Provisions for

Packages

Packing Instructions for Portable Tanks T4
Special Provisions for Portable Tanks TP1 TP29
IMDG EMS F-E, S-E
Stowage and Handling Category A



Segregation

Marine Pollutant

ICAO/IATA

IATA Proper Shipping Name FLAMMABLE LIQUID, N.O.S.

**Excepted Quantities** Passenger and Cargo Aircraft Limited Y344

Quantities Packing Instructions

Passenger and Cargo Aircraft Limited 10L

Quantities Max net Qty

Passenger and Cargo Aircraft Packing 355

Instructions

Passenger and Cargo Aircraft Max net 60L

Qty

Cargo Aircraft Packing Instructions 366 Cargo Aircraft Max net Qty 220L Special Provisions А3 Emergency Response Guidebook (ERG) 3L

Code Labels

Labels



# 14.4 Packing group

Packing group Ш

14.5 Environmental hazards

Environmental hazards Classified as a Marine Pollutant.

14.6 Special precautions for user

Special precautions for user Not known.

14.7 Maritime transport in bulk according to IMO instruments

No information available

# **SECTION 15: REGULATORY INFORMATION**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

European Regulations - Authorisations and/or Restrictions On Use

Candidate List of Substances of Very

High Concern for Authorisation

REACH: ANNEX XIV list of substances Not listed

subject to authorisation

use of certain dangerous substances,

mixtures and articles

REACH: Annex XVII Restrictions on the Polycyclic-aromatic hydrocarbons (PAH) (91-20-3), Paraffins (petroleum), manufacture, placing on the market and normal C5-20 (64771-72-8), Xylene (1330-20-7), ethylbenzene (100-41-4),

> Distillates (petroleum), hydrotreated light Kerosine - unspecified [A complex combination of hydrocarbons obtained by treating a petroleum fraction with

hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon





naphthalene (91-20-3), Xylene (1330-20-7)

Polycyclic aromatic hydrocarbons (PAHs) (91-20-3)

numbers predominantly in the range of C9 through C16 and boiling in the range  $\,$ 

of approximately 150 ° C to 290 ° C (302 ° F to 554 ° F).] (64742-47-8)

Community Rolling Action Plan

(CoRAP)

AP)

Regulation (EU)  $N^{\circ}$  2019/1021 of the European Parliament and of the Council

on persistent organic pollutants

Regulation (EC) N° 1005/2009 on Not listed

substances that deplete the ozone layer

Regulation (EU) N° 649/2012 of the Not listed

European Parliament and of the Council concerning the export and import of

hazardous chemicals

National regulations

Other Not known.

15.2 Chemical Safety Assessment

A REACH chemical safety assessment has not been carried out.

#### **SECTION 16: OTHER INFORMATION**

The following sections contain revisions or new statements:

#### **LEGEND**

Hazard Pictogram(s)







GHS08



GHS07



Hazard classification

Flam. Liq. 2: Flammable liquid, Category 2

Flam. Liq. 3: Flammable liquid, Category 3

Acute Tox. 4: Acute toxicity, Category 4

Asp. Tox. 1: Aspiration hazard, Category 1

Acute Tox. 4: Acute toxicity, Category 4

Skin Irrit. 2: Skin corrosion/irritation, Category 2

Eye Irrit. 2: Serious eye damage/irritation, Category 2

Acute Tox. 4: Acute toxicity, Category 4

STOT SE 3 : Specific target organ toxicity — single exposure, Category 3

Muta. 2: Germ cell mutagenicity, Category 2

Carc. 2 : Carcinogenicity, Category 2

Aquatic Acute 1: Hazardous to the aquatic environment, Acute, Category 1

 $\label{eq:chronic 1} \mbox{Aquatic Chronic 1: Hazardous to the aquatic environment, Chronic, Category 1}$ 



Aquatic Chronic 3: Hazardous to the aquatic environment, Chronic, Category 3

Hazard Statement(s)

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H341: Suspected of causing genetic defects.

H351: Suspected of causing cancer.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Precautionary Statement(s)

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233: Keep container tightly closed.

P240: Ground and bond container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/lighting/equipment.

P242: Use non-sparking tools.

P243: Take action to prevent static discharges.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P264: Wash hands and exposed skin thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTRE/doctor.

P302+P352: IF ON SKIN: Wash with plenty of water.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

Page: 13 - 15 Revision: 1 - Replaces:



Acronyms

## **ABRO Fuel Injector Cleaner**

P308+P313: IF exposed or concerned: Get medical advice/attention.

P312: Call a POISON CENTRE/doctor if you feel unwell.

P321: Specific treatment (see Medical Advice on this label).

P331: Do NOT induce vomiting.

P332+P313: If skin irritation occurs: Get medical advice/attention.

P337+P313: If eye irritation persists: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P370+P378: In case of fire: Use water spray, dry powder or carbon dioxide to extinguish.

P391: Collect spillage.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P403+P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

P501: Dispose of contents in accordance with local, state or national legislation.

 ${\sf ADN: European\ Agreement\ concerning\ the\ International\ Carriage\ of\ Dangerous}$ 

Goods by Inland Waterways

ADR: European Agreement concerning the International Carriage of Dangerous

Goods by Road

ATE : Acute Toxicity Estimate
CAS : Chemical Abstracts Service

CLP: Regulation (EC) No 1272/2008 on classification, labelling and packaging of

substances and mixtures

DNEL: Derived No Effect Level

EC: European Community

**EINECS**: European Inventory of Existing Commercial Chemical Substances

IATA: International Air Transport Association

IBC: Intermediate Bulk Container

ICAO : International Civil Aviation Organization
IMDG : International Maritime Dangerous Goods

LTEL: Long term exposure limit

PBT : Persistent, Bioaccumulative and Toxic PNEC : Predicted No Effect Concentration

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals RID: Regulations concerning the International Carriage of Dangerous Goods by

Rail

STEL : Short term exposure limit STOT : Specific Target Organ Toxicity

**UN**: United Nations

vPvB : very Persistent and very Bioaccumulative

Key literature references and sources for data used to compile the SDS Disclaimers

Regulation (EC) No. 1272/2008 (CLP)

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose.

Page: 14 - 15 Revision: 1 - Replaces:





Granville Oil & Chemicals Ltd gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Granville Oil & Chemicals Ltd accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Page: 15 - 15 Revision: 1 - Replaces: