

Granville Platinum Plus 10W/40

1 Litre, 5 Litre & 20 Litre

PRODUCT DESCRIPTION

Granville Platinum Plus 10W/40 is a high performance semi synthetic oil suitable for petrol and diesel engines including turbo, fuel injection and those fitted with catalytic converters.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

VW: 502.00 & 505.00
ACEA: A3/B4
API: SN/CF
MB: 229.3
Renault: RN0700 & RN0710

PRODUCT BENEFITS

- * Ensures lubricant performance
- * Excellent high & low temperature performance
- * Outstanding fuel efficiency
- * Effective environmental protection

PRODUCT USAGE

For engines where this specification of lubricant is required

DIRECTIONS FOR USE

As recommended by the engine manufacturer

STORAGE INSTRUCTIONS

Keep upright and sealed in a cool, dry place out of the reach of children



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	0045	5020618000457
5 Litre	0043	5020618000433
20 Litre	0295	5020618002956



Granville Platinum Plus 10W/40

1 Litre, 5 Litre & 20 Litre

SHELF LIFE

5 years from date of manufacture

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water
Percentage of Base Oil	: Less than 70%
Percentage of Biodiesel	: Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	12.5	<16.3	13.46
Viscosity, CCS -25°C	ASTM D4684	mPa.s		7000	
Total Base Number	ASTM D2896	mg KOH/g	10		11.25
Pour Point	ASTM D97	°C		-35	-33
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		12	
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			81.77
Density	ASTM D792	@ 15°C			0.872
Viscosity Index	ASTM D2270				160.96

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

