

# Granville Diesel Gold 15W/40

5 Litre

## PRODUCT DESCRIPTION

Granville Diesel Gold 15W/40 is a semi-synthetic engine oil for use in older engines requiring a lubricant of this grade.

## RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

VW: 505.00 & 502.00

ACEA: A3/B4

API: SN/CF

MB: 229.3



\* Image for illustrative purposes only.

## PRODUCT BENEFITS

- \* Ensures lubricant performance
- \* Excellent high & low temperature performance
- \* Outstanding fuel efficiency
- \* Effective environmental protection

## PRODUCT USAGE

For engines where this specification lubricant is required.

## DIRECTIONS FOR USE

As recommended by the engine manufacturer.

## STORAGE INSTRUCTIONS

Keep sealed in a cool, dry place.

## SHELF LIFE

5 years from date of manufacture.

|            |                  |
|------------|------------------|
| Appearance | : Amber liquid   |
| Odour      | : Characteristic |
| Solubility | : Insoluble      |



# Granville Diesel Gold 15W/40

5 Litre

| Test                         | Method     | Unit               | Min. | Max.  | Typical |
|------------------------------|------------|--------------------|------|-------|---------|
| Kinematic Viscosity at 100°C | ASTM D445  | mm <sup>2</sup> /s | 12.5 | <16.3 |         |
| Viscosity Index              | ASTM D2270 |                    | 80   |       |         |
| Cold Cranking Viscosity      | ASTM D4684 | mPa.s              |      | 7000  |         |
| Total Base Number            | ASTM D2896 | mg KOH/g           | 10   |       |         |
| Pour Point                   | ASTM D97   | °C                 |      | -27   |         |
| HTHS Viscosity               | ASTM D4683 | mPa.s              | 3.7  |       |         |
| NOACK Volatility             | ASTM D5800 | %                  |      | 13    |         |

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

