Granville

Multi-Purpose Grease

400g Cart, 500g Tin, 3kg, 12.5kg, 50kg, 400g Cart Norwegian & 400ml Norwegian

PRODUCT DESCRIPTION

A premium quality high melting point EP2 multi purpose grease with extreme pressure additives for use in all roller type anti-friction and plain bearings subjected to high load conditions. Used extensively for applications throughout industry and the automotive sector.



* Image for illustrative purposes only.

PRODUCT BENEFITS

* Excellent extreme pressure and anti-wear performance
* High degree of corrosion protection
* Highly versatile multi purpose grease

PRODUCT USAGE

Multi Purpose Grease can be applied manually by using a standard grease gun (400gm cartridges available) or via central lubricating system designed for, and capable of, pumping NLGI No 2 grease.

SIZE	PART NO	BARCODE
400g Cart	0122	5020618001225
500g Tin	0121	5020618001218
3kg	0187	5020618001874
12.5kg	0188	5020618001881
50kg	0189	5020618001898
400g Cart Norwegian	1635	N/A
400ml Norwegian	1831	N/A

DIRECTIONS FOR USE

As with all greases used for the first time, check compatibility with the grease applied previously and if necessary purge bearings prior to application. Likewise, as a general rule, take care not to over-lubricate and apply the quantity of grease recommended by the bearing manufacturer.

STORAGE INSTRUCTIONS

Store sealed in a cool dry place.

SHELF LIFE

5 years from date of manufacture.

HIGH PERFORMANCE
PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com

Granville

Multi-Purpose Grease

400g Cart, 500g Tin, 3kg, 12.5kg, 50kg, 400g Cart Norwegian & 400ml Norwegian

SPECIFICATION INFORMATION

* Operating temperature range: -20°C to + 140°C
* Melting point: 187°C
* Worked penetration: 265-295
* NLGI classification: 2
* Meets the approval of 267.0 Mercedes-Benz specification for service products

Appearance	:	Smooth dark brown grease
Odour	:	Characteristic
Solubility	:	Insoluble in water
Flammability	:	Not flammable at ambient temperatures

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS



Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com