

TECHNICAL DATA

Granville Multi-Purpose Grease

400g Cart, 500g Tin, 3kg, 12.5kg, 50kg, 400g Cart Norwegian & 400ml Norwegian

PRODUCT DESCRIPTION

A premium quality high melting point EP2 multi purpose grease with extreme pressure additives for use in all roller type anti-friction and plain bearings subjected to high load conditions. Used extensively for applications throughout industry and the automotive sector.

PRODUCT BENEFITS

- * Excellent extreme pressure and anti-wear performance
- * High degree of corrosion protection
- * Highly versatile multi purpose grease

© Granville MULTI NURPOSE SREASE WEARD WEAR WILTI PURPOSE GREASE

PRODUCT USAGE

Multi Purpose Grease can be applied manually by using a standard grease gun (400gm cartridges available) or via central lubricating system designed for, and capable of, pumping NLGI No 2 grease.

DIRECTIONS FOR USE

As with all greases used for the first time, check compatibility with the grease applied previously and if necessary purge bearings prior to application. Likewise, as a general rule, take care not to overlubricate and apply the quantity of grease recommended by the bearing manufacturer.

STORAGE INSTRUCTIONS

Store sealed in a cool dry place.

SHELF LIFE

5 years from date of manufacture.

* Image for illustrative purposes only.

	SIZE	PART NO	BARCODE
r	400g Cart	0122	5020618001225
	500g Tin	0121	5020618001218
	3kg	0187	5020618001874
	12.5kg	0188	5020618001881
	50kg	0189	5020618001898
	400g Cart Norwegian	1635	N/A
	400ml Norwegian	1831	N/A



Granville Oil & Chemicals Ltd. 29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL ENGLAND Tel: +44 (0)1709 890099 • www.granvilleoil.com



TECHNICAL DATA

Granville Multi-Purpose Grease

400g Cart, 500g Tin, 3kg, 12.5kg, 50kg, 400g Cart Norwegian & 400ml Norwegian

SPECIFICATION INFORMATION

- * Operating temperature range: -20°C to + 140°C
- * Melting point: 187°C
- * Worked penetration: 265-295
- * NLGI classification: 2
- * Meets the approval of 267.0 Mercedes-Benz specification for service products

Appearance	:	Smooth dark brown grease
Odour	:	Characteristic
Solubility	:	Insoluble in water
Flammability	:	Not flammable at ambient temperatures

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.



Granville Oil & Chemicals Ltd. 29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL ENGLAND Tel: +44 (0)1709 890099 • www.granvilleoil.com