

Granville

FS-VC 0W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

PRODUCT DESCRIPTION

Granville FS-VC 0W/30 is a fully synthetic engine oil formulated to meet the performance demands of modern petrol and diesel engines. FS-VC 0W/30 is a blend of the very latest in base oil and additive technology, designed for extended drain performance, especially suited for modern Volvo engines.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: A5/B5
API: SL/CF
Volvo: VCC 95200377
MB: 229.3

PRODUCT BENEFITS

- * Ensures lubricant performance over extended drain intervals
- * Excellent high & low temperature performance
- * Outstanding fuel efficiency
- * Effective environmental protection

PRODUCT USAGE

For engines where this specification and viscosity of lubricant is required.

DIRECTIONS FOR USE

As recommended by the engine manufacturer.

STORAGE INSTRUCTIONS

Keep upright and sealed in a cool, dry place out of the reach of children.



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	0522	5020618005223
5 Litre	0523	5020618005230
20 Litre	0516	5020618005162
199 Litre	0521	5020618005216



Granville

FS-VC 0W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

SHELF LIFE

5 years from date of manufacture.

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	9.3	<12.5	10.6
Total Base Number	ASTM D2896	mg KOH/g	8		12.9
HTHS Viscosity	ASTM D4683	mPa.s	2.9	<3.5	
NOACK Volatility	ASTM D5800	%		13	
Viscosity, CCS -35°C	ASTM D4684	mPa.s		6200	
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			58.9
Density	ASTM D792	@ 15°C			0.85
Pour Point	ASTM D97	°C		-40	
Viscosity Index	ASTM D2270				173

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

