

# Granville PU Flex Sealer

310ml Black

## PRODUCT DESCRIPTION

Granville PU Flex is a one component moisture curing, high modulus polyurethane sealant and adhesive for a wide range of bonding and sealing applications. PU Flex once cured can be overpainted with all paint types.

## PRODUCT BENEFITS

- \* Strong adhesive and bonder
- \* Overpaintable

## PRODUCT USAGE

For bonding and sealing automotive panels and trim.

## DIRECTIONS FOR USE

Joints must be sound, clean, dry and free from oil and grease. Curing compound and any other foreign matter must be thoroughly removed.

Remove end cap from cartridge, pierce top and apply nozzle, trim the nozzle at 45° slightly larger than the joint to be sealed. Apply using a standard cartridge gun keeping even pressure on the trigger. Clean excess uncured sealant away with white spirit.

## STORAGE INSTRUCTIONS

Store in original sealed packaging, at temperatures between +5°C and + 25°C

## SHELF LIFE

Unopened 12 months from date of manufacture.



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
310ml Black	0980	5020618009801



# Granville PU Flex Sealer

310ml Black

## SPECIFICATION INFORMATION

Temperature resistance: -30°C to +80°C

Skinning Time: 80 mins

Curing Speed: 3mm per 24 hours

**Appearance** : Coloured Polyurethane paste

**Odour** : Characteristic - solvent

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

