

# Granville

## Hypalube SN SS 10W/40

1 Litre, 5 Litre, 20 Litre & 199 Litre

### PRODUCT DESCRIPTION

Granville Hypalube SN 10W/40 is a high performance semi synthetic oil suitable for petrol and diesel engines, including turbo-charged, fuel injected and those fitted with catalytic converters.

### RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

VW: 502.00 & 505.00  
ACEA: A3/B4  
API: SN/CF  
MB: 229.3  
Renault: RN0700 & RN0710



\* Image for illustrative purposes only.

### PRODUCT BENEFITS

- \* Ensures lubricant performance
- \* Excellent high & low temperature performance
- \* Outstanding fuel efficiency
- \* Effective environmental protection

### PRODUCT USAGE

For engines where this specification lubricant is required.

### DIRECTIONS FOR USE

As recommended by the engine manufacturer.

### STORAGE INSTRUCTIONS

Keep sealed in a cool, dry place.

### SHELF LIFE

5 years from date of manufacture.

**Appearance** : Amber liquid

SIZE	PART NO	BARCODE
1 Litre	0095	5020618000952
5 Litre	0123	5020618001232
20 Litre	0263	5020618002635
199 Litre	991B	5020618099208



# Granville

## Hypalube SN SS 10W/40

1 Litre, 5 Litre, 20 Litre & 199 Litre

**Odour** : Characteristic

**Solubility** : Insoluble in water

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	12.5	<16.3	13.46
Viscosity, CCS -25°C	ASTM D4684	mPa.s		7000	
Total Base Number	ASTM D2896	mg KOH/g	10		11.25
Pour Point	ASTM D97	°C		-35	-33
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		12	
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			81.77
Density	ASTM D792	@ 15°C			0.872
Viscosity Index	ASTM D2270				160.96

### SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

### TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

