

# Granville Hypalube PR 20W/50

1 Litre, 4.25 Litre, 20 Litre & 199 Litre

## PRODUCT DESCRIPTION

Granville Hypalube PR 20W/50 is a multigrade engine oil formulated to meet the requirements of older petrol and diesel engines.

## RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: SE/CC

## PRODUCT BENEFITS

- \* Suitable for petrol & diesel engines
- \* Can be used in plant & agricultural machinery

## PRODUCT USAGE

For engines where this specification lubricant is required.

## DIRECTIONS FOR USE

As recommended by the engine manufacturer.

## STORAGE INSTRUCTIONS

Store sealed and upright in a cool dry place out of the reach of children.

## SHELF LIFE

5 years from date of manufacture.

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water
Percentage of Biodiesel	: Nil



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	0144	5020618001447
4.25 Litre	0146	5020618001461
20 Litre	0096	5020618000969
199 Litre	0125	5020618001256



# Granville Hypalube PR 20W/50

1 Litre, 4.25 Litre, 20 Litre & 199 Litre

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	16.3	<21.9	19.66
Viscosity, CCS -15°C	ASTM D4684	mPa.s		9500	
HTHS Viscosity	ASTM D4683	mPa.s	3.7		
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			181.7
Density	ASTM D792	@ 15°C			0.882
Total Base Number	ASTM D2896	mg KOH/g			7.98

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

