

Granville Hypalube PR 20W/50

1 Litre, 4.25 Litre, 20 Litre & 199 Litre

PRODUCT DESCRIPTION

Granville Hypalube PR 20W/50 is a multigrade engine oil formulated to meet the requirements of older petrol and diesel engines.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: SE/CC

PRODUCT BENEFITS

- * Suitable for petrol & diesel engines
- * Can be used in plant & agricultural machinery

PRODUCT USAGE

For engines where this specification lubricant is required.

DIRECTIONS FOR USE

As recommended by the engine manufacturer.

STORAGE INSTRUCTIONS

Store sealed and upright in a cool dry place out of the reach of children.

SHELF LIFE

5 years from date of manufacture.

| | |
|-------------------------|----------------------|
| Appearance | : Amber liquid |
| Odour | : Characteristic |
| Solubility | : Insoluble in water |
| Percentage of Biodiesel | : Nil |



* Image for illustrative purposes only.

| SIZE | PART NO | BARCODE |
|------------|---------|---------------|
| 1 Litre | 0144 | 5020618001447 |
| 4.25 Litre | 0146 | 5020618001461 |
| 20 Litre | 0096 | 5020618000969 |
| 199 Litre | 0125 | 5020618001256 |



Granville Hypalube PR 20W/50

1 Litre, 4.25 Litre, 20 Litre & 199 Litre

| Test | Method | Unit | Min. | Max. | Typical |
|------------------------------|------------|--------------------|------|-------|---------|
| Kinematic Viscosity at 100°C | ASTM D445 | mm ² /s | 16.3 | <21.9 | 19.66 |
| Cold Cranking Viscosity | ASTM D4684 | mPa.s | | 9500 | |
| HTHS Viscosity | ASTM D4683 | mPa.s | 3.7 | | |
| Kinematic Viscosity at 40°C | ASTM D445 | mm ² /s | | | 181.7 |
| Density | ASTM D792 | @ 15°C | | | 0.882 |
| Total Base Number | ASTM D2896 | mg KOH/g | | | 7.98 |

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

