

### TECHNICAL DATA

## Autosol Roadster 20W/50

5 Litre

#### PRODUCT DESCRIPTION

Autosol Roadster 20W/50 is a conventional multigrade engine oil designed to preserve and protect classic engines. Specially blended using high quality mineral oils and selected additives making it ideally suited to older technology, particularly 60's, 70's and 80's classic car engines.

### RECOMMENDED FOR USE BY AUTOSOL FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: SE/CC

#### **PRODUCT BENEFITS**

- \* Ideally suited to classic engines
- \* Ensures lubricant performance
- \* Excellent high & low temperature performance



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
5 Litre	0392	5020618003922

#### PRODUCT USAGE

For engines where this specification lubricant is required.

#### **DIRECTIONS FOR USE**

As recommended by the engine manufacturer.

#### STORAGE INSTRUCTIONS

Keep sealed in a cool, dry place.

#### SHELF LIFE

5 years from date of manufacture.

Revision: 1 | Date: 16/03/2012

Appearance : Amber liquid

Odour : Characteristic

Solubility : Insoluble in water

Flammability : >200°C





## TECHNICAL DATA

# Autosol Roadster 20W/50

5 Litre

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm²/s	16.3	<21.9	19.66
Viscosity, CCS -15°c	ASTM D4684	mPa.s		9500	
HTHS Viscosity	<b>ASTM D4683</b>	mPa.s	3.7		
Viscosity, Kinematic 40°c	ASTM D445	mm²/s			181.7
Density	ASTM D792	@ 15°c			0.882
Total Base Number	<b>ASTM D2896</b>	mg KOH/g			7.98

#### **SAFETY PRECAUTIONS**

Revision: 1 | Date: 16/03/2012

Please see our latest EC Safety Data Sheets for details.

#### TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

