Granville
Hypalube 30 Mineral
1 Litre, 5 Litre, 20 Litre & 199 Litre



* Image for illustrative purposes only.

PRODUCT DESCRIPTION

Granville Hypalube SAE 30 motor oil is a monograde engine oil formulated for vintage and classic 4 stroke petrol engines, plant and garden machinery where SAE 30 lubricant is recommended.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: SF/CC
SAE: 30

PRODUCT BENEFITS

* Monograde SAE 30 engine oil
* Excellent high & low temperature performance

PRODUCT USAGE

For engines where this specification lubricant is required.

DIRECTIONS FOR USE

As recommended by the engine manufacturer.

STORAGE INSTRUCTIONS

Keep sealed in a cool, dry place.

SHELF LIFE

5 years from date of manufacture.

SIZE	PART NO	BARCODE
1 Litre	1819	5020618018193
5 Litre	1802	5020618018025
20 Litre	1832	5020618018322
199 Litre	1820	5020618018209

Appearance : Amber liquid

HIGH PERFORMANCE
PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com

Granville

Hypalube 30 Mineral

1 Litre, 5 Litre, 20 Litre & 199 Litre

Odour : Characteristic

Solubility : Insoluble in water

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm^2/s	9.3	<12.5	10.57
HTHS Viscosity	ASTM D4683	mPa.s	2.9		
Viscosity, Kinematic 40°c	ASTM D445	mm^2/s			89.87
Density	ASTM D792	@ 15°c			0.876
Total Base Number	ASTM D2896	mg KOH/g			6.22
Viscosity Index	ASTM D2270		75		
Pour Point	ASTM D97	°c		-15	

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

HIGH PERFORMANCE PREMIUM QUALITY

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com