

# Granville Hypalube 30 Mineral

1 Litre, 5 Litre, 20 Litre & 199 Litre

## PRODUCT DESCRIPTION

Granville Hypalube SAE 30 motor oil is a monograde engine oil formulated for vintage and classic 4 stroke petrol engines, plant and garden machinery where SAE 30 lubricant is recommended.

## RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: SF/CC

SAE: 30

## PRODUCT BENEFITS

- \* Monograde SAE 30 engine oil
- \* Excellent high & low temperature performance

## PRODUCT USAGE

For engines where this specification lubricant is required.

## DIRECTIONS FOR USE

As recommended by the engine manufacturer.

## STORAGE INSTRUCTIONS

Keep sealed in a cool, dry place.

## SHELF LIFE

5 years from date of manufacture.

**Appearance** : Amber liquid



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	1819	5020618018193
5 Litre	1802	5020618018025
20 Litre	1832	5020618018322
199 Litre	1820	5020618018209



# Granville Hypalube 30 Mineral

1 Litre, 5 Litre, 20 Litre & 199 Litre

**Odour** : Characteristic

**Solubility** : Insoluble in water

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	9.3	<12.5	10.57
HTHS Viscosity	ASTM D4683	mPa.s	2.9		
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			89.87
Density	ASTM D792	@ 15°C			0.876
Total Base Number	ASTM D2896	mg KOH/g			6.22
Viscosity Index	ASTM D2270		75		
Pour Point	ASTM D97	°C		-15	

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

