

# Granville Blue Gasket Sealant

40g Norwegian

## PRODUCT DESCRIPTION

Granville Blue Gasket Sealant is a new technology sealant which is free from the solvent problems of other formulations and stays flexible when cured. Blue Gasket Sealant cures to a non-hardening consistency forming an instant seal that will not crack, chip or flake making it ideal for sealing metal-to-metal joints where a gasket is not required. Use on cylinder heads, sumps, pumps, gearboxes, axles, hydraulic and pneumatic assemblies.

## PRODUCT BENEFITS

- \* New advanced non-setting formulation
- \* Stays flexible
- \* Resists petrol, steam, antifreeze, oils, common solvents and most chemicals
- \* Methylene Chloride free



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
40g Norwegian	1696	N/A

## PRODUCT USAGE

Ideal for sealing metal-to-metal joints where a gasket is not required. Use on cylinder heads, sumps, pumps, gearboxes, axles, hydraulic and pneumatic assemblies.

## DIRECTIONS FOR USE

Remove cap from tube and pierce end. Ensure that parts to be fitted are clean, dry and free from oil & grease, apply a continuous bead around the area, leave for 5-10 minutes then join the surfaces together.

## STORAGE INSTRUCTIONS

Store sealed in a cool, dry place out of direct sunlight and away from sources of heat.

## SHELF LIFE

2 years from date of manufacture.



# Granville Blue Gasket Sealant

40g Norwegian

## SPECIFICATION INFORMATION

Operating Temperature: -50°C to + 150°C

Gap Fill: 0.5mm

Full Cure Time: 24 hours (with heat)

Pressure Rating: Up to 10,000 psi

<b>Appearance</b>	: Clear blue liquid/gel
<b>Odour</b>	: Characteristic - solvent
<b>Specific Gravity</b>	: 1.2
<b>Flammability</b>	: Flammable as a liquid/gel.

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

