

TECHNICAL DATA

Granville Silicone Grease

70g Tube

PRODUCT DESCRIPTION

Granville Silicone Grease is compounded from dimethyl polysiloxane fluid, the product has a broad temperature range and is chemically inert, being resistant to water (hot,cold, steam & brine), lubricating oils, most hydrocarbons & solvents, natural gas, refinery gases and many acidic solutions.

PRODUCT USAGE

Granville Silicone Grease has been designed for the lubrication of cylinder slides, taps, valves & stopcocks (where the presence of chemicals & solvents mean that conventional products can not be used). The product is suitable for use as a damping compound - both under conditions of high pressure and elevated temperature. Excellent dielectric properties of the grease means the product can be used with high voltage electrical systems for lubricating non-conducting contacts, prevents corona discharge and for preventing flashover on high voltage anodes.



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
70g Tube	0073	5020618000730

STORAGE INSTRUCTIONS

Store sealed in a cool, dry place.

SHELF LIFE

3 years from date of manufacture.

SPECIFICATION INFORMATION

Operating temperature: -40°C to +200°C

NLGI classification: 2

Revision: 2 | Date: 19/07/2016

Dielectric strength: 20Kv/mm (approx)

Appearance : Smooth white semi-translucent gel

Odour : Characteristic
Solubility : Insoluble in water





TECHNICAL DATA

Granville Silicone Grease

70g Tube

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

