

TECHNICAL DATA

Granville Lithium L2M – 5th Wheel Grease

12.5kg

PRODUCT DESCRIPTION

Granville 5th Wheel Grease is a tenacious grease designed for heavy duty applications where adhesion, shock loading and good corrosion protection is needed. It has been proven ideal for the use on fifth wheels on articulated lorries, but has also found use in other applications such as bucket pins on heavy earth moving equipment, crane slews, and also as an assembly and running compound.

PRODUCT BENEFITS

- * Excellent adhesion
- * High level of lubricating solids
- * Long lasting protection

PRODUCT USAGE	SIZE	PART NO	BARCODE
	12.5kg	174K	N/A
For applications where adhesion, shock loading and good corrosion			

For applications where adhesion, shock loading and good corrosion — protection is needed.

STORAGE INSTRUCTIONS

Stored sealed in a cool, dry place.

SHELF LIFE

Ρ

3 years from date of manufacture.

SPECIFICATION INFORMATION

Operating Temperature: -20°C to +140°C NLGI No: 2/3 Worked Penetration: 250 to 295

Appearance

: Grey/black smooth adhesive grease



* Image for illustrative purposes only.

GRANVILLE

FIFTH WHEEL

GREASE

	Granville Oil & Chemicals Ltd.
20 Caldtharna Ind	Fat Caldtharpa Datharbara CC

Revision: 2 | Date: 19/07/2016

29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL ENGLAND Tel: +44 (0)1709 890099 • www.granvilleoil.com



TECHNICAL DATA

Granville Lithium L2M – 5th Wheel Grease

12.5kg

Odour Solubility Characteristic

Insoluble in water

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.



Granville Oil & Chemicals Ltd. 29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL ENGLAND Tel: +44 (0)1709 890099 • www.granvilleoil.com