

Granville LS 80W/90

1 Litre & 5 Litre

PRODUCT DESCRIPTION

Granville LS 80W/90 is a specially formulated extreme pressure gear oil for optimum performance of limited slip differentials. LS 80W/90 is a blend of high quality base oils, performance EP additives and specially selected friction modifiers to provide a lubricant with exacting requirements for limited slip operations.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: GL-5



* Image for illustrative purposes only.

PRODUCT BENEFITS

- * Reduces whining and chattering
- * Ensures clutch plates slide smoothly
- * Outstanding extremes of temperature protection

SIZE	PART NO	BARCODE
1 Litre	1636	5020618016366
5 Litre	1715	5020618017158

PRODUCT USAGE

Suitable for limited slip differentials fitted to cars, vans, trucks, buses and agricultural equipment.

DIRECTIONS FOR USE

As recommended by the vehicle manufacturer.

STORAGE INSTRUCTIONS

As recommended by the vehicle manufacturer.

SHELF LIFE

5 years from date of manufacture.

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water



Granville LS 80W/90

1 Litre & 5 Litre

Percentage of Base Oil : More Than 70%

Percentage of Biodiesel : Nil

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s	13.5	<18.5	15.98
Kinematic Viscosity at 40°C	ASTM D445	mm ² /s			153.42
Density	ASTM D792	@ 15°C			0.893

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

