

# TECHNICAL DATA

# Granville LS 80W/90

1 Litre & 5 Litre

#### **PRODUCT DESCRIPTION**

Granville LS 80W/90 is a specially formulated extreme pressure gear oil for optimum performance of limited slip differentials. LS 80W/90 is a blend of high quality base oils, performance EP additives and specially selected friction modifiers to provide a lubricant with exacting requirements for limited slip operations.

## RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS API: GL-5

### **PRODUCT BENEFITS**

- \* Reduces whining and chattering
- \* Ensures clutch plates slide smoothly
- \* Outstanding extremes of temperature protection

## **PRODUCT USAGE**

Suitable for limited slip differentials fitted to cars, vans, trucks, buses and agricultural equipment.

#### **DIRECTIONS FOR USE**

As recommended by the vehicle manufacturer.

#### **STORAGE INSTRUCTIONS**

As recommended by the vehicle manufacturer.

## SHELF LIFE

5 years from date of manufacture.

#### Appearance

: Amber liquid



\* Image for illustrative purposes only.

| SIZE    | PART NO | BARCODE       |
|---------|---------|---------------|
| 1 Litre | 1636    | 5020618016366 |
| 5 Litre | 1715    | 5020618017158 |



Granville Oil & Chemicals Ltd. 29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL ENGLAND Tel: +44 (0)1709 890099 • www.granvilleoil.com



# TECHNICAL DATA

# Granville LS 80W/90

1 Litre & 5 Litre

| Odour                   | : | Characteristic     |
|-------------------------|---|--------------------|
| Solubility              | : | Insoluble in water |
| Percentage of Base Oil  | : | More Than 70%      |
| Percentage of Biodiesel | : | Nil                |

| Test                       | Method    | Unit   | Min. | Max.  | Typical |
|----------------------------|-----------|--------|------|-------|---------|
| Viscosity, Kinematic 100°c | ASTM D445 | mm²/s  | 13.5 | <18.5 | 15.98   |
| Viscosity, Kinematic 40°c  | ASTM D445 | mm²/s  |      |       | 153.42  |
| Density                    | ASTM D792 | @ 15°c |      |       | 0.893   |

# SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

# **TRANSPORT CLASSIFICATION**

Please see our latest EC Safety Data Sheets for details.



Granville Oil & Chemicals Ltd. 29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL ENGLAND Tel: +44 (0)1709 890099 • www.granvilleoil.com