

# Granville Two Stroke

500ml, 1 Litre, 5 Litre & 20 Litre

## PRODUCT DESCRIPTION

Granville Two Stroke is formulated for use in two stroke engines with oil injection or premix systems. The low ash, clean burn characteristics reduce carbon build up, prevent pre-ignition plug fouling and reduce smoke emissions. Two Stroke may also be used in garden machinery.

## RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: TC  
JASO: FB

## PRODUCT BENEFITS

- \* Low ash formulation
- \* For oil injection or premix systems
- \* Low smoke formulation

## PRODUCT USAGE

For two stroke engines where this specification oil is recommended.

## DIRECTIONS FOR USE

As per the engine manufacturers recommendations.

## DOSAGE INFORMATION

Always check engine manufactures recommendations for mixing ratios.

## STORAGE INSTRUCTIONS

Store sealed in a cool, dry place.



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
500ml	0120	5020618001201
1 Litre	0118	5020618001188
5 Litre	0176	5020618001768
20 Litre	0271	5020618002710



# Granville Two Stroke

500ml, 1 Litre, 5 Litre & 20 Litre

## SHELF LIFE

5 years from date of manufacture.

<b>Appearance</b>	: Red liquid
<b>Odour</b>	: Characteristic
<b>Solubility</b>	: Insoluble in water

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	6.5		9.52
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			72
Density	ASTM D792	@ 15°C			0.879
Total Base Number	ASTM D2896	mg KOH/g			1.5
Pour Point	ASTM D97	°C			-21
Viscosity Index	ASTM D2270				110

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

