

Granville Chainsaw Oil

1 Litre, 5 Litre & 20 Litre

PRODUCT DESCRIPTION

Granville Chainsaw Oil is a superior quality anti-fling oil recommended for all chainsaws. Chainsaw Oil reduces friction wear and extends the working life of the blade.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

SAE: 30

PRODUCT BENEFITS

- * Anti-fling formulation
- * Extends working life of the blade

DIRECTIONS FOR USE

As per machine manufacturers handbook.

STORAGE INSTRUCTIONS

Store sealed in a cool, dry place.

SHELF LIFE

5 years from date of manufacture.

| | |
|-------------------|----------------------|
| Appearance | : Amber liquid |
| Odour | : Characteristic |
| Solubility | : Insoluble in water |



* Image for illustrative purposes only.

| SIZE | PART NO | BARCODE |
|----------|---------|---------------|
| 1 Litre | 1031 | 5020618010319 |
| 5 Litre | 0429 | 5020618004295 |
| 20 Litre | 0448 | 5020618004486 |



Granville Chainsaw Oil

1 Litre, 5 Litre & 20 Litre

| Test | Method | Unit | Min. | Max. | Typical |
|------------------------------|------------|--------------------|------|-------|---------|
| Kinematic Viscosity at 100°C | ASTM D445 | mm ² /s | 9.3 | <12.5 | 11.41 |
| HTHS Viscosity | ASTM D4683 | mPa.s | 2.9 | | |
| Kinematic Viscosity at 40°C | ASTM D445 | mm ² /s | | | 100.32 |
| Density | ASTM D792 | @ 15°C | | | 0.884 |

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

