Granville
Cylinder Black
100ml & 250ml



* Image for illustrative purposes only.

PRODUCT DESCRIPTION

Granville Cylinder Black is a single component, silicone modified alkyd based paint designed specifically for use on surfaces subjected to high operating temperatures. Granville Cylinder Black air dries at room temperature to form a tough satin black film which matches OEM finishes. The paint cures with the application of heat in service.

PRODUCT BENEFITS

* Single component paint
* Air Dries
* Satin Black finish

PRODUCT USAGE

Granville Cylinder Black is specifically designed for use in automotive applications where resistance to heat in service is required i.e. cylinder heads, exhaust manifolds turbocharger casings etc.

SIZE	PART NO	BARCODE
100ml	0246	5020618002468
250ml	0060	5020618000600

DIRECTIONS FOR USE

Ensure surfaces to be painted are clean, dry and free from wax, oil and grease. Rusted surfaces should be wire brushed to remove loose rust etc. Clean shiny surfaces should be abraded to provide a key for the paint. The use of a primer prior to application of Granville Cylinder Black is not recommended.
Stir the product thoroughly before use then apply coat evenly by brush using multi-directional strokes. Apply the paint thinly and evenly, application of thick coats is not recommended as this can lead to cracking and wrinkling of the paint at high temperatures. It is not recommended to apply more than one coat.
Use white spirit or commercial brush cleaner to clean brushes after use.

HIGH PERFORMANCE
PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com

Granville
Cylinder Black
100ml & 250ml

STORAGE INSTRUCTIONS
Store in a cool , dry place away from direct sunlight and sources of ignition.

SHELF LIFE
18 months from date of manufacture.

SPECIFICATION INFORMATION
Temperature Resistance: 450°C Max

Appearance	:	Black paint
Odour	:	Characteristic
Specific Gravity	:	1.04 @ 15.6°C (Typical)
Solubility	:	Insoluble in water
Flammability	:	Flammable
VOC	:	VOC in g/l 2004/42/II.I(i):660g/l(2007)./500g/l(2010) Product contains 400g/l

SAFETY PRECAUTIONS
Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION
Please see our latest EC Safety Data Sheets for details.

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS



Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com