

# Granville Competition (Fully Synthetic Two Stroke)

1 Litre

## PRODUCT DESCRIPTION

Granville Competition 2-Stroke is a fully synthetic 2-Stroke oil formulated for performance 2-Stroke motorcycles and high performance scooters offering extremely good performance. Competition Two Stroke contains Granville's unique SQ-20 friction modifier which gives ultimate protection.

## RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

JASO: FC  
ISO-L-EGD

## PRODUCT BENEFITS

- \* Fully synthetic
- \* Unique SQ-20 friction modifier added
- \* For high performance two stroke motorcycles and scooters

## PRODUCT USAGE

For two stroke engines where this grade of oil is recommended.

## DIRECTIONS FOR USE

Use as per the engine manufacturers recommendations.

## STORAGE INSTRUCTIONS

Store sealed in a cool, dry place.

## SHELF LIFE

5 years from date of manufacture.

**Appearance** : Green liquid



\* Image for illustrative purposes only.

| SIZE    | PART NO | BARCODE       |
|---------|---------|---------------|
| 1 Litre | 0603    | 5020618006039 |



# Granville Competition (Fully Synthetic Two Stroke)

1 Litre

**Odour** : Characteristic  
**Solubility** : Insoluble in water

| Test                       | Method     | Unit               | Min. | Max. | Typical |
|----------------------------|------------|--------------------|------|------|---------|
| Viscosity, Kinematic 100°C | ASTM D445  | mm <sup>2</sup> /s | 6.5  |      | 9.5     |
| Viscosity, Kinematic 40°C  | ASTM D445  | mm <sup>2</sup> /s |      |      | 59.3    |
| Viscosity Index            | ASTM D2270 |                    |      |      | 143     |
| Density                    | ASTM D792  | @ 15°C             |      |      | 0.892   |
| Total Base Number          | ASTM D2896 | mg KOH/g           |      |      | 1.6     |
| Pour Point                 | ASTM D97   | °C                 |      |      | -19     |

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

