

Granville ATF Dexron VI

1 Litre, 5 Litre & 20 Litre

PRODUCT DESCRIPTION

Granville ATF Dexron VI is a specially formulated low viscosity fully synthetic, high performance automatic transmission fluid formulated to withstand and protect against extreme wear and heat build up offering smoother gear change.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

GM: Dexron VI & 1940773

Ford: Mercon#174; LV

Toyota: WS

Nissan: Matic S, Matic J, Matic K, Matic 402 & Matic D

Saab: 93 165 147

Honda: DW-1 & ATF-Z1

Hyundai: ATF SP-IV & NWS-9638

Kia: ATF SP-IV

Mitsubishi: ATF SP-IV & ATF J2

JWS: 3324

Aisin Warner: AW-1

JASO: 1-A

MB: 236.10, 236.12, 236.14, 236.41 & 236.17

BMW/Mini: 83 22 2 152 426

Suzuki: 3314 & 3317

VW: G 052 162, G 052 990, G 055 162 & G 060 162

Volvo: 97341



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	1569	5020618015697
5 Litre	1570	5020618015703
20 Litre	1592	5020618015925

PRODUCT BENEFITS

- * Low viscosity formulation
- * Fully synthetic
- * Excellent heat & wear control.

PRODUCT USAGE

For vehicles were this specification product is recommended.



Granville ATF Dexron VI

1 Litre, 5 Litre & 20 Litre

DIRECTIONS FOR USE

As per the vehicle manufacturers recommendations.

STORAGE INSTRUCTIONS

Keep sealed in a cool, dry place.

SHELF LIFE

5 years from date of manufacture.

SPECIFICATION INFORMATION

GM: Dexron VI
Ford: Mercon LV
JASO: 1-A
Aisin Warner: AW-1. Honda: DW-1
Hyundai/Kia: SP-IV
Hyundai: NWS-9638. JWS 3324.
Mitsubishi: SP-IV, ATF J2.
Nissan: Matic-S. Saab: 93 165 147
Toyota: WS

Appearance	: Red liquid
Odour	: Characteristic
Solubility	: Insoluble in water
Flammability	: >200°C

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	4.5	6.4	6.2
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s		32	
Viscosity, CCS	ASTM D4684	mPa.s		3200	



Granville ATF Dexron VI

1 Litre, 5 Litre & 20 Litre

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

