Granville
ATF Dexron VI

1 Litre, 5 Litre & 20 Litre



* Image for illustrative purposes only.

PRODUCT DESCRIPTION

Granville ATF Dexron VI is a specially formulated low viscosity fully synthetic, high performance automatic transmission fluid formulated to withstand and protect against extreme wear and heat build up offering smoother gear change.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

GM: Dexron VI & 1940773
Ford: Mercon® LV
Toyota: WS
Nissan: Matic S, Matic J, Matic K, Matic 402 & Matic D
Saab: 93 165 147
Honda: DW-1 & ATF-Z1
Hyundai: ATF SP-IV & NWS-9638
Kia: ATF SP-IV
Mitsubishi: ATF SP-IV & ATF J2
JWS: 3324
Aisin Warner: AW-1
JASO: 1-A
MB: 236.10, 236.12, 236.14, 236.41 & 236.17
BMW/Mini: 83 22 2 152 426
Suzuki: 3314 & 3317
VW: G 052 162, G 052 990, G 055 162 & G 060 162
Volvo: 97341

SIZE	PART NO	BARCODE
1 Litre	1569	5020618015697
5 Litre	1570	5020618015703
20 Litre	1592	5020618015925

PRODUCT BENEFITS

* Low viscosity formulation
* Fully synthetic
* Excellent heat & wear control.

PRODUCT USAGE

For vehicles were this specification product is recommended.

HIGH PERFORMANCE
PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com

Granville
ATF Dexron VI

1 Litre, 5 Litre & 20 Litre

DIRECTIONS FOR USE

As per the vehicle manufacturers recommendations.

STORAGE INSTRUCTIONS

Keep sealed in a cool, dry place.

SHELF LIFE

5 years from date of manufacture.

SPECIFICATION INFORMATION

GM: Dexron VI
Ford: Mercon LV
JASO: 1-A
Aisin Warner: AW-1. Honda: DW-1
Hyundai/Kia: SP-IV
Hyundai: NWS-9638. JWS 3324.
Mitsubishi: SP-IV, ATF J2.
Nissan: Matic-S. Saab: 93 165 147
Toyota: WS

Appearance	:	Red liquid

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS



Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com

Granville
ATF Dexron VI

1 Litre, 5 Litre & 20 Litre

Odour : Characteristic

Solubility : Insoluble in water

Flammability : >200°C

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm^2/s	4.5	6.4	6.2
Viscosity, Kinematic 40°c	ASTM D445	mm^2/s		32	
Viscosity, CCS	ASTM D4684	mPa.s		0	

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

HIGH PERFORMANCE PREMIUM QUALITY

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com