

Granville CVT Fluid

1 Litre, 5 Litre & 205 Litre

PRODUCT DESCRIPTION

Granville CVT Fluid is a fully synthetic formulation blended from the highest quality base oils and additives to give a high performance multi vehicle CVT (continuously variable transmission) fluid that is suitable for use in both belt or chain driven systems. The superior formulation shows excellent anti-shudder durability, good shear stability and anti-foam properties.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

VAG: TL 52180, G 052 180, G 052 516, TL 052 516 & TL 52116

Ford: CVT30, CVT23, Mercon C & WSS-M2C928-A

Honda: HMMF & HVF-2

Toyota: TC & CVTF FE

Nissan: NS-2, NS-1, NS-3 & NS-2V

Mitsubishi: CVTF-J1, SPIII, Lineartronic CVTF, i-CVT F,

Lineartronic CV-30 & Lineartronic CVTF II

Subaru: NS-2

Mini: EZL 799

Hyundai: CVTF

Suzuki: TC, NS-2, CVT Green 1 & CVTF Green 2

Jeep: NS-2 & DEX-CVT

MB: 236.20

Hyundai/Kia: SP CVT-1

JWS: 3320

Mazda: CVTF 3320 & JWS 3320



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	1565	5020618015659
5 Litre	1566	5020618015666
205 Litre	1568	5020618015680

PRODUCT BENEFITS

- * Excellent anti-shudder durability
- * Good shear stability
- * Excellent anti-foam characteristics
- * Suitable for use with belt or chain driven systems



Granville CVT Fluid

1 Litre, 5 Litre & 205 Litre

PRODUCT USAGE

For vehicles where this specification of CVT fluid is recommended.
This product is NOT suitable for Ford & Toyota hybrid CVT units.

DIRECTIONS FOR USE

As per the vehicle manufacturers recommendations.

STORAGE INSTRUCTIONS

Store sealed in a cool, dry place

SHELF LIFE

5 years from date of manufacture

SPECIFICATION INFORMATION

VAG TL 52180, G052 180
Ford: CVT30, CVT 23, Mercon C
Honda: HMMF
Toyota: TC
Nissan: NS-1, NS-2, NS-3
Mitsubishi: CVTF-J1, SP III
Subaru: NS-2, Lineartronic CVTF
BMW Mini: EZL 799. Hyundai: CVTF
Suzuki: TC, NS-2, CVT Green 1,
Jeep: NS-2. DEX-CVT.
MB:236.20

Appearance	: Red liquid
Odour	: Characteristic
Solubility	: Insoluble in water
Flammability	: >200°C



Granville CVT Fluid

1 Litre, 5 Litre & 205 Litre

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	6.5	8.5	7.5
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			35

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

