Granville
CVT Fluid
1 Litre, 5 Litre & 205 Litre



* Image for illustrative purposes only.

PRODUCT DESCRIPTION

Granville CVT Fluid is a fully synthetic formulation blended from the highest quality base oils and additives to give a high performance multi vehicle CVT (continuously variable transmission) fluid that is suitable for use in both belt or chain driven systems. The superior formulation shows excellent anti-shudder durability, good shear stability and anti-foam properties.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

VW: TL 521 80, G 052 180, G 052 516, TL 052 516 & TL 521 16
Ford: CVT30, CVT23, Mercon® C, WSS-M2C928-A, M2C933-A & e-CVT
Honda: HMMF & HCF-2
Toyota: TC & CVTF FE
Nissan: NS-2, NS-1, NS-3, NS-2V & N-CVT
Mitsubishi: CVTF-J1, SPIII & CVTF-J4
Subaru: NS-2, Lineartronic CV-30, Lineartronic CVTF, Lineartronic CVTF II & Lineartronic i-CVT FG
Mini: EZL 799
Hyundai: CVTF
Suzuki: TC, NS-2, CVT Green 1 & CVTF Green 2
Jeep: NS-2 & DEX-CVT
MB: 236.20
Hyundai/Kia: SP CVT-1
JWS: 3320
Mazda: CVTF 3320 & JWS 3320

SIZE	PART NO	BARCODE
1 Litre	1565	5020618015659
5 Litre	1566	5020618015666
205 Litre	1568	5020618015680

PRODUCT BENEFITS

* Excellent anti-shudder durability
* Good shear stability
* Excellent anti-foam characteristics
* Suitable for use with belt or chain driven systems

HIGH PERFORMANCE
PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com

Granville
CVT Fluid
1 Litre, 5 Litre & 205 Litre

PRODUCT USAGE

For vehicles where this specification of CVT fluid is recommended.
This product is NOT suitable for Ford & Toyota hybrid CVT units.

DIRECTIONS FOR USE

As per the vehicle manufacturers recommendations.

STORAGE INSTRUCTIONS

Store sealed in a cool, dry place

SHELF LIFE

5 years from date of manufacture

Appearance	:	Red liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS



Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com

Granville
CVT Fluid
1 Litre, 5 Litre & 205 Litre

Flammability : >200°C

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm^2/s	6.5	8.5	7.5
Viscosity, Kinematic 40°c	ASTM D445	mm^2/s			35

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS



Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com