Granville®
More than just an oil company

TECHNICAL DATA

Revision: 5 | Date: 17/01/2023

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville

Hypalube C2 FS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

PRODUCT DESCRIPTION

Granville Hypalube C2 5W/30 is a new generation, fully synthetic multi-grade engine oil formulated to meet the performance demands of low emission engines which combine high performance, fuel efficiency and emission control. Manufactured to a Mid SAPS (Sulphated ash, phosphorous and sulphur content) formulation. Recommended for all engine types where the manufacturer specifies a C2 oil.
It is imperative that the correct oil is used as costly repairs will be required if the wrong specification of lubricant is used.
NOTE: This oil is NOT suitable for Vehicles that require Low Speed Pre-ignition (LSPI) capabilities. Suitable for vehicle up to 2017.



* Image for illustrative purposes only.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C2
PSA: B71 2290 (<2017)
API: SN/CF

SIZE	PART NO	BARCODE
1 Litre	0704	5020618007043
5 Litre	0705	5020618007050
20 Litre	0709	5020618007098
199 Litre	0708	5020618007081

PRODUCT BENEFITS

* Mid SAPS (Sulphated ash, phosphorous and sulphur content) formulation
* Fully Synthetic

PRODUCT USAGE

Use where recommended by the engine manufacturer

DIRECTIONS FOR USE

Use as required by the engine manufacturer

HIGH PERFORMANCE
PREMIUM QUALITY

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com

Granville

Hypalube C2 FS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

STORAGE INSTRUCTIONS

Store sealed and upright in a cool dry place out of the reach of children

SHELF LIFE

5 years form date of manufacture

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm^2/s	9.3	<12.5	11
Viscosity, CCS -30°c	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	6		8.9
Pour Point	ASTM D97	°c		-35	
HTHS Viscosity	ASTM D4683	mPa.s	2.9	3.5	
NOACK Volatility	ASTM D5800	%		11	
Viscosity, Kinematic 40°c	ASTM D445	mm^2/s			67
Density	ASTM D792	@ 15°c			0.85
Viscosity Index	ASTM D2270				156

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

HIGH PERFORMANCE
PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com