Granville®
More than just an oil company

TECHNICAL DATA

Revision: 6 | Date: 23/11/2017

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville
ATF 1375.4

1 Litre, 5 Litre & 20 Litre

PRODUCT DESCRIPTION

Granville ATF 1375.4 is a superior quality fully synthetic transmission fluid specially developed for the 6HP series ZF transmissions used in passenger cars. ATF 1375.4 is formulated to prevent the build up of heat within the transmission whilst protecting the components, producing a smooth gear change and preventing friction.



* Image for illustrative purposes only.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ATF: M-1375.4
BMW: 83220142516, 83220144137 & 83222305396 (ATF2)
Ford: Mercon® SP & Mercon® SP XT-6-QSP
Jaguar: C2C 8432
Land Rover: TYK 500050
VW: G 055 005-A1, G 055 005-A2 & G 055 005-A6
ZF: Lifeguard 6+, S671 090 252, S671 090 253 & S671 090 255

SIZE	PART NO	BARCODE
1 Litre	1544	5020618015444
5 Litre	1545	5020618015451
20 Litre	1549	5020618015499

PRODUCT BENEFITS

* Fully synthetic
* Excellent heat control
* Smooth gear changing, no judder or lag.

PRODUCT USAGE

For use in 6HP series ZF automatic transmissions.

DIRECTIONS FOR USE

Use as recommended by the transmission manufacturer

HIGH PERFORMANCE
PREMIUM QUALITY

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com

Granville
ATF 1375.4
1 Litre, 5 Litre & 20 Litre

STORAGE INSTRUCTIONS

Store seal and upright in a cool dry place out of the reach of children.

SHELF LIFE

5 Years from date of manufacture

SPECIFICATION INFORMATION

Suitable for use in vehicles that require the following specifications: ATF M-1375.4, BMW: 83220142516,83220144137,83222305396 (ATF2), Ford: Mercon SP XT-6-QSP, Jaguar: C2C 8432, Land Rover: TYK 500050, VAG: G 055 005 A1/A2/A6, ZF S671 090 252/3/5, ZF Lifeguard 6

Appearance	:	Pale Gold liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Flammability	:	>200°C

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

HIGH PERFORMANCE PREMIUM QUALITY

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com

Granville
ATF 1375.4
1 Litre, 5 Litre & 20 Litre

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm^2/s			6.9
Viscosity, Kinematic 40°c	ASTM D445	mm^2/s			36.34
Density	ASTM D792	@ 15°c			0.846

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS



Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com