

TECHNICAL DATA

Granville ATF 1375.4

1 Litre, 5 Litre & 20 Litre

PRODUCT DESCRIPTION

Granville ATF 1375.4 is a superior quality fully synthetic transmission fluid specially developed for the 6HP series ZF transmissions used in passenger cars. ATF 1375.4 is formulated to prevent the build up of heat within the transmission whilst protecting the components, producing a smooth gear change and preventing friction.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ATF: M-1375.4

BMW: 83220142516, 83220144137 & 83222305396 (ATF2)

Ford: Mercon® SP & Mercon® SP XT-6-QSP

Jaguar: C2C 8432

Land Rover: TYK 500050

VW: G 055 005-A1, G 055 005-A2 & G 055 005-A6

ZF: Lifeguard 6+, S671 090 252, S671 090 253 & S671 090 255

PRODUCT BENEFITS

- * Fully synthetic
- * Excellent heat control
- * Smooth gear changing, no judder or lag.

PRODUCT USAGE

For use in 6HP series ZF automatic transmissions.

DIRECTIONS FOR USE

Revision: 6 | Date: 23/11/2017

Use as recommended by the transmission manufacturer



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	1544	5020618015444
5 Litre	1545	5020618015451
20 Litre	1549	5020618015499





TECHNICAL DATA

Granville ATF 1375.4

1 Litre, 5 Litre & 20 Litre

STORAGE INSTRUCTIONS

Store seal and upright in a cool dry place out of the reach of children.

SHELF LIFE

5 Years from date of manufacture

SPECIFICATION INFORMATION

Suitable for use in vehicles that require the following specifications: ATF M-1375.4, BMW:

83220142516,83220144137,83222305396 (ATF2), Ford: Mercon SP XT-6-QSP, Jaguar: C2C 8432, Land Rover: TYK 500050, VAG: G 055

005 A1/A2/A6, ZF S671 090 252/3/5, ZF Lifeguard 6

Appearance : Pale Gold liquid

Odour : Characteristic

Solubility : Insoluble in water

Flammability : >200°C

Revision: 6 | Date: 23/11/2017





TECHNICAL DATA

Granville ATF 1375.4

1 Litre, 5 Litre & 20 Litre

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm²/s			6.9
Viscosity, Kinematic 40°c	ASTM D445	mm²/s			36.34
Density	ASTM D792	@ 15°c			0.846

SAFETY PRECAUTIONS

Revision: 6 | Date: 23/11/2017

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

