

## Veedol Sintron C3 5W/30

1 Litre & 5 Litre

### PRODUCT DESCRIPTION

Veedol Sintron C3 5W-30 is a universal, synthetic, fuel economy motor oil developed according to the most recent technology. Formulated using specially selected synthetic base oils with high viscosity index and a well-balanced choice of advanced additives which helps achieve the following: improved fuel efficiency; high and shear stable viscosity index; excellent low temperature fluidity ensuring easy cold start; effective lubrication at very high temperatures; unique detergent/dispersion additive system ensuring engine cleanliness with negligible sludge; reduced formation of combustion ashes; very strong protection against wear, corrosion and foaming.

Veedol Sintron C3 5W-30 is specially developed for passenger car unit injector diesel engines. Moreover this lubricant is suitable for use in petrol and diesel engines, with or without turbo-charging. This product meets the requirements of several OEM's and thus has a wide application range.

### OEM APPROVALS

BMW: LL-04  
 MB-Approval: 229.51 & 229.52  
 VW: 505.00 & 505.01  
 GM: dexos 2

### RECOMMENDED FOR USE BY VEEDOL FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C3  
 API: SN

### PRODUCT BENEFITS

- \* OEM Approved product
- \* Improved fuel efficiency
- \*\* Effective lubrication at very high temperatures



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	5000	5020618050001
5 Litre	5001	5020618050018



## Veedol Sintron C3 5W/30

1 Litre & 5 Litre

### PRODUCT USAGE

Recommended for applications where this grade and specification of lubricant is required

### DIRECTIONS FOR USE

Use as per the engine manufacturers handbook

### STORAGE INSTRUCTIONS

Store sealed and upright in a cool dry place out of the reach of children

### SHELF LIFE

5 years from date of manufacture

<b>Appearance</b>	: Amber oily liquid
<b>Odour</b>	: Characteristic
<b>Solubility</b>	: Insoluble in water

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	9.3	<12.5	12.195
Total Base Number	ASTM D2896	mg KOH/g	10		
Pour Point	ASTM D97	°C		<-36	
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		10	
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			69.55
Density	ASTM D792	@ 15°C			0.85
Viscosity, CCS -30°C	ASTM D4684	mPa.s		6600	

### SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.



# Veedol Sintron C3 5W/30

1 Litre & 5 Litre

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

