

# Granville FS-NX 0W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

## PRODUCT DESCRIPTION

Granville FS-NX 0W/30 is a highly advanced fully synthetic engine oil formulated to give the most advanced protection and performance under all operating conditions giving increased fuel economy and extended service intervals. FS-NX is suitable for use in petrol and diesel engines with and without turbos where the manufacturer recommends this grade and specification of lubricant.

Note: Not suitable for diesel engines with 2 or 3 turbochargers.

## RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C2

BMW: LL-12 FE

## PRODUCT BENEFITS

\*Increased fuel economy

\*Extended service intervals

## PRODUCT USAGE

Not suitable for engines with 2 or 3 turbochargers

## DIRECTIONS FOR USE

Use as per manufacturer's recommendations

## STORAGE INSTRUCTIONS

Store sealed in a cool, dry place out of the reach of children.

## SHELF LIFE

5 years from date of manufacture

**Appearance** : Amber liquid

**Odour** : Characteristic



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	1059	5020618010593
5 Litre	1060	5020618010609
20 Litre	1061	5020618010616
199 Litre	1064	5020618010647



# Granville FS-NX 0W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

**Solubility** : Insoluble in water

**Percentage of Biodiesel** : Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	9.3	<12.5	11
Viscosity, CCS -35°C	ASTM D4684	mPa.s		6200	
Total Base Number	ASTM D2896	mg KOH/g	7		8
HTHS Viscosity	ASTM D4683	mPa.s	2.9	<3.5	
NOACK Volatility	ASTM D5800	%		11	
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			58.7
Density	ASTM D792	@ 15°C			0.85
Viscosity Index	ASTM D2270				183

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

