Granville
More than just an oil company

TECHNICAL DATA

Revision: 1 | Date: 16/02/2018

Granville

Hypalube VL FS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre



* Image for illustrative purposes only.

PRODUCT DESCRIPTION

Hypalube VL 5W/30 is a fully synthetic engine oil formulated to provide outstanding performance levels both in terms of engine cleanliness and fuel economy. The product is recommended by Granville Oil & Chemicals Ltd for use in Volkswagen, Audi, Seat and Skoda engines requiring a VW specification oil. Hypalube VL 5W/30 is fully compatible with exhaust after treatment devices such as diesel particulate filters.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C3
VW: 504.00 & 507.00
API: SN/CF
BMW: LL-04
MB: 229.51
Porsche: C30

SIZE	PART NO	BARCODE
1 Litre	1127	5020618011279
5 Litre	1128	5020618011286
20 Litre	1129	5020618011293
199 Litre	1132	5020618011323

PRODUCT BENEFITS

* Effective environmental protection
* Outstanding fuel efficiency
* Excellent high & low temperature performance
* Ensures lubricant performance over extended drain intervals

PRODUCT USAGE

VAG engine types.

DIRECTIONS FOR USE

As recommended by the engine manufacturer

HIGH PERFORMANCE
PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com

Granville

Hypalube VL FS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

STORAGE INSTRUCTIONS

Keep sealed in a cool, dry place

SHELF LIFE

5 years from date of manufacture

Appearance : Amber liquid

Odour : Characteristic

Solubility : Insoluble in water

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm^2/s	9.3	<12.5	12.4
Total Base Number	ASTM D2896	mg KOH/g	7		9.7
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
Viscosity, CCS -30°c	ASTM D4684	mPa.s		6600	
Pour Point	ASTM D97	°c		-36	
NOACK Volatility	ASTM D5800	%		<10	
Viscosity, Kinematic 40°c	ASTM D445	mm^2/s			76.8
Density	ASTM D792	@ 15°c			0.85
Viscosity Index	ASTM D2270				159

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

HIGH PERFORMANCE
PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com