

TECHNICAL DATA

G+Pro Ceramic Grease

150ml

PRODUCT DESCRIPTION

G + PRO Ceramic Grease is a specially formulated lubricant designed with high heat conductivity. It can be used in a variety of areas where heat resistance is important, such as car brake pads and exhaust manifold studs. It can also protect against rust and corrosion, whilst providing lubrication to moving parts. It has excellent adhesion to metallic surfaces.

PRODUCT BENEFITS

- * Excellent adhesion
- * Heat resistant
- * Excellent heat conductivity

PRODUCT USAGE

* For use where heat resistance is a must

DIRECTIONS FOR USE

1.Shake can well before use2.Remove dirt, grease and water from area to be sprayed for best results3.Hold can 15cm away and spray4.Wipe away excess

STORAGE INSTRUCTIONS

This aerosol should be stored out of direct sunlight and below 50°C.

SHELF LIFE

24 months unopened, 6 months once opened

| Appearance | : | White thickened liquid |
|------------------|---|------------------------|
| Odour | : | Characteristic |
| Specific Gravity | : | 0.76 |
| Solubility | : | Insoluble in water |



| * | Image | for | illustrative | nurnoses | only | v |
|---|--------|-----|--------------|----------|------|----|
| | innaye | 101 | mustrative | pulpuses | UIII | y. |

| SIZE | PART NO | BARCODE |
|-------|---------|---------------|
| 150ml | 1079 | 5020618010791 |



Granville Oil & Chemicals Ltd. 29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL ENGLAND Tel: +44 (0)1709 890099 • www.granvilleoil.com



TECHNICAL DATA

G+Pro Ceramic Grease

150ml

| Flammability | : | Highly flammable |
|--------------|---|------------------|
| VOC | : | 270g per litre |

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.



Granville Oil & Chemicals Ltd. 29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL ENGLAND Tel: +44 (0)1709 890099 • www.granvilleoil.com