Granville
More than just an oil company

TECHNICAL DATA

Revision: 1 | Date: 17/01/2023

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville

Hypafleet E9 10W/30

20 Litre & 199 Litre

PRODUCT DESCRIPTION

Hypalube Hypafleet E9 10W/30 is a high performing heavy duty diesel engine oil that has been formulated using high performance additives and high quality base oils to produce a mid SAPS (sulphated ash, Phosphorus and Sulphur) engine oil that is suitable for vehicles equipped with diesel particulate filers (DPF?S) exhaust gas recirculation (EGR) and selective catalytic reduction (SCR) systems. This engine oil is suitable for mixed fleet applications including Euro IV, V and VI engine types.



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
20 Litre	6444	5020618064442
199 Litre	6446	5020618064466

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: E7 & E9
API: CJ-4, CK-4 & SN
CAT: ECF-3
Cummins: 20086
Detroit Diesel: 93K222
DEUTZ: DQC III-10 LA & DQC III-18 LA
Ford: WSS-M2C171-F1
MB: 228.31
MTU Type 2.1
Scania: Low Ash
Volvo: VDS-4.5

PRODUCT BENEFITS

*Multi fleet applications
*Mid SAPS
*Prevents heat and carbon build up

PRODUCT USAGE

For use where this grade and specification of oil is required

HIGH PERFORMANCE
PREMIUM QUALITY

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com

Granville
Hypafleet E9 10W/30
20 Litre & 199 Litre

DIRECTIONS FOR USE
Use as per the engine manufacturers recommendations

STORAGE INSTRUCTIONS
Store sealed and upright in a coll dry place and out of the reach of children

SHELF LIFE
5 years from date of manufacture

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Base Oil	:	80.00%
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm^2/s	9.3	<12.5	12
Viscosity, CCS -25°c	ASTM D4684	mPa.s		7000	
Total Base Number	ASTM D2896	mg KOH/g	9		11.7
Pour Point	ASTM D97	°c		-27	
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		12	
Viscosity, Kinematic 40°c	ASTM D445	mm^2/s			77.4
Density	ASTM D792	@ 15°c			0.86
Viscosity Index	ASTM D2270				152

SAFETY PRECAUTIONS
Please see our latest EC Safety Data Sheets for details.

HIGH PERFORMANCE
PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com

Granville

Hypafleet E9 10W/30

20 Litre & 199 Litre

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS



Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com