

Granville MTF M 75W/80

1 Litre, 5 Litre & 20 Litre

PRODUCT DESCRIPTION

Mineral gear oil formulated to meet the specific requirements of manual gear boxes.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: GL-4
 PSA: B71 2330
 GM: 1940768
 Volvo: 97308
 MIL: MIL-L-2105 D
 VW: G 052 512 & G 055 512
 Esso: EZL 848



* Image for illustrative purposes only.

PRODUCT BENEFITS

- * Excellent oxidation stability
- * Outstanding low & high temperature performance
- * Ensures the synchromesh functions correctly
- * Protect against corrosion
- * Long life
- * Excellent wear protection

PRODUCT USAGE

For gearboxes that require EP 75W/80 lubricant

DIRECTIONS FOR USE

Use as per the manufacturers recommendations

STORAGE INSTRUCTIONS

Store sealed and upright in a cool dry place away from the reach of children

SIZE	PART NO	BARCODE
1 Litre	1638	5020618016380
5 Litre	1717	5020618017172
20 Litre	1720	5020618017202



Granville MTF M 75W/80

1 Litre, 5 Litre & 20 Litre

SHELF LIFE

5 years from date of manufacture

Appearance	:	Amber fluid
Odour	:	Characteristic
Solubility	:	Insoluble in water

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	7	<11	9.52
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			52.53
Density	ASTM D792	@ 15°C			0.867

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

