Granville®
More than just an oil company

TECHNICAL DATA

Revision: 2 | Date: 12/05/2016

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville

MTF M 75W/80

1 Litre, 5 Litre & 20 Litre



* Image for illustrative purposes only.

PRODUCT DESCRIPTION

Mineral gear oil formulated to meet the specific requirements of manual gear boxes.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: GL-4
PSA: B71 2330
GM: 1940768
Volvo: 97308
MIL: MIL-L-2105 D
VW: G 052 512 & G 055 512
Esso: EZL 848

SIZE	PART NO	BARCODE
1 Litre	1638	5020618016380
5 Litre	1717	5020618017172
20 Litre	1720	5020618017202

PRODUCT BENEFITS

* Excellent oxidation stability
* Outstanding low & high temperature performance
* Ensures the synchromesh functions correctly
* Protect against corrosion
* Long life
* Excellent wear protection

PRODUCT USAGE

For gearboxes that require EP 75W/80 lubricant

DIRECTIONS FOR USE

Use as per the manufacturers recommendations

STORAGE INSTRUCTIONS

Store sealed and upright in a cool dry place away from the reach of children

HIGH PERFORMANCE
PREMIUM QUALITY

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com

Granville
MTF M 75W/80

1 Litre, 5 Litre & 20 Litre

SHELF LIFE

5 years from date of manufacture

Appearance : Amber fluid
Odour : Characteristic
Solubility : Insoluble in water

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm^2/s	7	<11	9.52
Viscosity, Kinematic 40°c	ASTM D445	mm^2/s			52.53
Density	ASTM D792	@ 15°c			0.867

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

HIGH PERFORMANCE PREMIUM QUALITY

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com