

# Granville MTF M 75W/80

1 Litre, 5 Litre & 20 Litre

## PRODUCT DESCRIPTION

Mineral gear oil formulated to meet the specific requirements of manual gear boxes.

## RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: GL-4  
PSA: B71 2330  
GM: 1940768  
Volvo: 97308  
MIL: MIL-L-2105 D  
VW: G 052 512 & G 055 512  
Esso: EZL 848



\* Image for illustrative purposes only.

## PRODUCT BENEFITS

- \* Excellent oxidation stability
- \* Outstanding low & high temperature performance
- \* Ensures the synchromesh functions correctly
- \* Protect against corrosion
- \* Long life
- \* Excellent wear protection

## PRODUCT USAGE

For gearboxes that require EP 75W/80 lubricant

## DIRECTIONS FOR USE

Use as per the manufacturers recommendations

## STORAGE INSTRUCTIONS

Store sealed and upright in a cool dry place away from the reach of children

SIZE	PART NO	BARCODE
1 Litre	1638	5020618016380
5 Litre	1717	5020618017172
20 Litre	1720	5020618017202



# Granville MTF M 75W/80

1 Litre, 5 Litre & 20 Litre

## SHELF LIFE

5 years from date of manufacture

<b>Appearance</b>	: Amber fluid
<b>Odour</b>	: Characteristic
<b>Solubility</b>	: Insoluble in water

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	7	<11	9.52
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			52.53
Density	ASTM D792	@ 15°C			0.867

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

