

Granville Hypafleet E9 5W/30

20 Litre & 199 Litre

PRODUCT DESCRIPTION

Hypalube Hypafleet E9 5W/30 is a high performance fuel efficient heavy duty diesel engine oil that has been formulated using superior additives and quality base oils to produce a mid - low SAPS (sulphated ash, Phosphorus and Sulphur) engine oil that is suitable for use with exhaust after treatment systems including DPFs and SCR/EGR NOX reducing systems including the use of Adblue. This engine oil is suitable for mixed fleet applications including Euro IV, V and VI engine types.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: E4, E6, E7 & E9
 API: CJ-4 & CK-4
 MB: 228.51
 Mack: EO-OPP
 MAN: 3677
 MTU Type 3.1
 Renault Truck: RLD-3
 Volvo: VDS-4
 Scania: LDF-4

PRODUCT BENEFITS

- *Fully Synthetic
- *Low SAPS (sulphated ash, Phosphorus and Sulphur)
- * Ideal for Euro IV, V and VI engine types.

PRODUCT USAGE

For use in engines where this grade and specification oil is required.

DIRECTIONS FOR USE

Use as per the manufacturers instructions



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
20 Litre	6423	5020618064237
199 Litre	6425	5020618064251



Granville Hypafleet E9 5W/30

20 Litre & 199 Litre

STORAGE INSTRUCTIONS

Store sealed and upright in a cool place out of the reach of children.

SHELF LIFE

5 years from date of manufacture.

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water
Percentage of Base Oil	: 80.00%
Percentage of Biodiesel	: Nil

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s	9.3	<12.5	
Cold Cranking Viscosity	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	12		
Pour Point	ASTM D97	°C		-40	
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		12	

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

