

## Granville Hypafleet E7 10W/40

20 Litre & 199 Litre

### PRODUCT DESCRIPTION

Hypalube Hypafleet E7 10W/40 is a semi synthetic long drain engine oil providing excellent engine protection against heat and engine wear even under the most severe of driving conditions. Ideal use in modern commercial fleet diesel engines both turbo charged and naturally aspirated.

### RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: E7  
API: CI-4  
CAT: ECF-2  
Global: DHD-1  
Mack: EO-M+ & EO-N  
MAN: 3275  
MB: 228.3  
MTU Type 2  
Renault Truck: RXD & RLD-2  
Volvo: VDS-3  
Cummins: CES 20077 & CES 20078  
DEUTZ: DQC III-5 & DQC III-10  
DAF: Extended Drain

### PRODUCT BENEFITS

- \*Mixed Fleet applications
- \*Outstanding wear protection
- \*Long drain capabilities

### PRODUCT USAGE

For use where the engine manufacturer recommends this grade and specification of oil



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
20 Litre	6451	5020618064510
199 Litre	6453	5020618064534



# Granville Hypafleet E7 10W/40

20 Litre & 199 Litre

## DIRECTIONS FOR USE

As per the engine manufacturers instruction

## STORAGE INSTRUCTIONS

Store sealed and upright in a cool place and away from children

## SHELF LIFE

5 years from date of manufacture

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water
Percentage of Base Oil	: 79.00%
Percentage of Biodiesel	: Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	12.5	<16.3	
Viscosity, CCS -25°C	ASTM D4684	mPa.s		7000	
Total Base Number	ASTM D2896	mg KOH/g	10		
HTHS Viscosity	ASTM D4683	mPa.s	3.7		
NOACK Volatility	ASTM D5800	%		12	

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

