

## Granville Hypafleet E7 15W/40

5 Litre, 20 Litre & 199 Litre

### PRODUCT DESCRIPTION

Hypafleet E7 15W/40 is a wide ranging heavy duty engine oil suitable for use in commercial, agricultural and off-highway applications. The combination of quality additives and superior base oils make this oil suitable for use in both naturally aspirated and turbo charged engine types.

### RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: E7  
 API: CI-4  
 CAT: ECF-1-A & ECF-2  
 Cummins: CES 20076, CES 20077 & CES 20078  
 Global: DHD-1  
 Mack: EO-N  
 MAN: 3275  
 MB: 228.3  
 MTU Type 2  
 Renault Truck: RLD-2  
 Volvo: VDS-3



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
5 Litre	6464	5020618064640
20 Litre	6465	5020618064657
199 Litre	6467	5020618064671

### PRODUCT BENEFITS

- \*Suitable for both Commercial and Agricultural applications
- \*ideal Multi-fleet users
- \*Superior engine wear protection

### PRODUCT USAGE

For engines requiring this grade and specification of engine oil

### DIRECTIONS FOR USE

Use as per the manufacturers recommendations



# Granville Hypafleet E7 15W/40

5 Litre, 20 Litre & 199 Litre

## STORAGE INSTRUCTIONS

Store sealed and upright in a cool, dry place and out of the reach of children

## SHELF LIFE

5 years from date of manufacture

<b>Appearance</b>	: Amber liquid
<b>Odour</b>	: Characteristic
<b>Solubility</b>	: Insoluble in water
<b>Percentage of Base Oil</b>	: 80.00%
<b>Percentage of Biodiesel</b>	: Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	12.5	<16.3	
Viscosity, CCS -20°C	ASTM D4684	mPa.s		7000	
Total Base Number	ASTM D2896	mg KOH/g	10		
Pour Point	ASTM D97	°C		-27	
HTHS Viscosity	ASTM D4683	mPa.s	3.7		
NOACK Volatility	ASTM D5800	%		13	

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

