

# Granville Hy-Vis Hydraulic 68

20 Litre & 199 Litre

## PRODUCT DESCRIPTION

Hypalube Hy-Vis 68 hydraulic oil is formulated for use in a wide range of agricultural, commercial and industrial applications, it offers excellent pumpability and protects against oxidation and corrosion.

## RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

AFNOR: NF E 48603

David Brown: S1.53.101

Denison Filterability: TP02100

DIN: 51524 Part 2 (HLP)

Vickers: 1.286.S & 1.286.S3



\* Image for illustrative purposes only.

## PRODUCT BENEFITS

\*Excellent pumpability

\*Protects against oxidation and corrosion.

SIZE	PART NO	BARCODE
20 Litre	0725	5020618007258
199 Litre	0009	5020618000099

## STORAGE INSTRUCTIONS

Store Upright and sealed in a cool place and out of the reach of children

## SHELF LIFE

5 Years from date of manufacture

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water
Percentage of Biodiesel	: Nil



# Granville Hy-Vis Hydraulic 68

20 Litre & 199 Litre

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s	61.2	74.8	67.64
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s			8.79
Density	ASTM D792	@ 15°C			0.874

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

