



Granville

Hy-Vis Hydraulic 68

20 Litre & 199 Litre

PRODUCT DESCRIPTION

Hyalube Hy-Vis 68 hydraulic oil is formulated for use in a wide range of agricultural, commercial and industrial applications, it offers excellent pumpability and protects against oxidation and corrosion.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

- AFNOR: NF E 48603
- David Brown: S1.53.101
- Denison Filterability: TP02100
- DIN: 51524 Part 2 (HLP)
- Vickers: 1.286.S & 1.286.S3

PRODUCT BENEFITS

- *Excellent pumpability
- *Protects against oxidation and corrosion.

STORAGE INSTRUCTIONS

Store Upright and sealed in a cool place and out of the reach of children

SHELF LIFE

5 Years from date of manufacture

Appearance : Amber liquid



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
20 Litre	0725	5020618007258
199 Litre	0009	5020618000099



Granville

Hy-Vis Hydraulic 68

20 Litre & 199 Litre

Odour	: Characteristic
Solubility	: Insoluble in water
Percentage of Biodiesel	: Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s	61.2	74.8	67.64
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s			8.79
Density	ASTM D792	@ 15°C			0.874

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

