

## Granville Hy-Vis Hydraulic 100


20 Litre & 199 Litre

### PRODUCT DESCRIPTION

Hyalube Hy-vis 100 hydraulic oil is formulated for use in a wide range of agricultural, commercial and industrial applications, it offers excellent pumpability and protects against oxidation and corrosion.

### RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

AFNOR: NF E 48603  
David Brown: S1.53.101  
Denison Filterability: TP02100  
DIN: 51524 Part 2  
Vickers: 1.286.S & 1.286.S3



\* Image for illustrative purposes only.

### PRODUCT BENEFITS

- \*Excellent pumpability
- \*Protects against oxidation and corrosion.

SIZE	PART NO	BARCODE
20 Litre	0726	5020618007265
199 Litre	179B	5020618023395

### STORAGE INSTRUCTIONS

Store upright and sealed in a cool place and out of the reach of children

### SHELF LIFE

5 years from date of manufacture

<b>Appearance</b>	: Amber liquid
<b>Odour</b>	: Characteristic
<b>Solubility</b>	: Insoluble in water
<b>Percentage of Biodiesel</b>	: Nil



# Granville Hy-Vis Hydraulic 100

20 Litre & 199 Litre

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s	90	110	92.54
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s			10.64
Density	ASTM D792	@ 15°C			0.881

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

